NO. OF COPIES RECEIVED			Form C-103
	-	,	Supersedes Old
DISTRIBUTION	- NEW MEXICO ON COL	ICEDYATION COMMECION	C-102 and C-103
SANTA FE	NEW MEXICO OIL CON	ISERVATION COMMISSION	Effective 1-1-65
FILE			Eq. Indicate Time of I are
U.S.G.S.			5a. Indicate Type of Lease
LAND OFFICE			State X Fee
OPERATOR			5, State Oil & Gas Lease No.
	•		L 245
SUNI (DO NOT USE THIS FORM FOR	DRY NOTICES AND REPORTS OF PROPOSALS TO DRILL OR TO DEEPEN OR PLUS CATION FOR PERMIT - " (FORM C-101) FOR S	N WELLS BACK TO A DIFFERENT RESERVOIR. BUCH PROPOSALS.	
1.			7. Unit Agreement Name
WELL X WELL	OTHER-		
2. Name of Operator			8. Farm or Lease Name
Dalport Oil Corp.			State-C
3. Address of Operator			9. Well No.
3471 First National	Bank Bldg., Dallas, TX		2
4. Location of Well			10. Field and Pool, or Wildcat
IINIT LETTER E	1650 FEET FROM THE north	LINE AND 330 FEET FROM	Double L Queen-Assoc.
UNIT GETTER	The state of the s	1112 1110	
THE West LINE. SE	CTION 16 TOWNSHIP 15S	RANGE 30E NMPM	
,,,,			
	15. Elevation (Show wheth	er DF, RT, GR, etc.)	12. County
			Chaves
16.	1. Assessment Description	Name of Maria - Dinama - O	
	k Appropriate Box To Indicate	-	
NOTICE OF	FINTENTION TO:	SUBSEQUEN	T REPORT OF:
	-	_	. —
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON		COMMENCE DRILLING OPNS.	PLUG AND ABANDONMENT
PULL OR ALTER CASING	CHANGE PLANS	CASING TEST AND CEMENT JOB X	
-		T	
		OTHER	
OTHER	۲ ۲	OTHER	
OTHER	*		
	Operations (Clearly state all pertinent d		g estimated date of starting any proposed
17, Describe Proposed or Completed work) SEE RULE 1603.	d Operations (Clearly state all pertinent d		g estimated date of starting any proposed
	i Operations (Clearly state all pertinent d		g estimated date of starting any proposed
work) SEE RULE 1103.		etails, and give pertinent dates, includin	
Spud Aug. 13,	1975, 11:30 AM. Cemented	etails, and give pertinent dates, including the state of used 8 5/8"-28#	casing at 330° with
Spud Aug. 13,		etails, and give pertinent dates, including the state of used 8 5/8"-28#	
Spud Aug. 13, 175 sx "c" + 2	1975, 11:30 AM. Cemented % c.c. circulated 50 sx.	etails, and give pertinent dates, including the state of used 8 5/8"-28#	casing at 330° with
Spud Aug. 13,	1975, 11:30 AM. Cemented % c.c. circulated 50 sx.	etails, and give pertinent dates, including the state of used 8 5/8"-28#	casing at 330° with
Spud Aug. 13, 175 sx "c" + 2	1975, 11:30 AM. Cemented % c.c. circulated 50 sx.	etails, and give pertinent dates, including the state of used 8 5/8"-28#	casing at 330° with
Spud Aug. 13, 175 sx "c" + 2	1975, 11:30 AM. Cemented % c.c. circulated 50 sx.	etails, and give pertinent dates, including the state of used 8 5/8"-28#	casing at 330° with
Spud Aug. 13, 175 sx "c" + 2	1975, 11:30 AM. Cemented % c.c. circulated 50 sx.	etails, and give pertinent dates, including the state of used 8 5/8"-28#	casing at 330° with
Spud Aug. 13, 175 sx "c" + 2	1975, 11:30 AM. Cemented % c.c. circulated 50 sx.	etails, and give pertinent dates, including the state of used 8 5/8"-28#	casing at 330° with
Spud Aug. 13, 175 sx "c" + 2	1975, 11:30 AM. Cemented % c.c. circulated 50 sx.	etails, and give pertinent dates, including the state of used 8 5/8"-28#	casing at 330° with
Spud Aug. 13, 175 sx "c" + 2	1975, 11:30 AM. Cemented % c.c. circulated 50 sx.	etails, and give pertinent dates, including the state of used 8 5/8"-28#	casing at 330° with
Spud Aug. 13, 175 sx "c" + 2	1975, 11:30 AM. Cemented % c.c. circulated 50 sx.	etails, and give pertinent dates, including the state of used 8 5/8"-28#	casing at 330° with
Spud Aug. 13, 175 sx "c" + 2	1975, 11:30 AM. Cemented % c.c. circulated 50 sx.	etails, and give pertinent dates, including the state of used 8 5/8"-28#	casing at 330° with
Spud Aug. 13, 175 sx "c" + 2	1975, 11:30 AM. Cemented % c.c. circulated 50 sx.	etails, and give pertinent dates, including the state of used 8 5/8"-28#	casing at 330° with
Spud Aug. 13, 175 sx "c" + 2	1975, 11:30 AM. Cemented % c.c. circulated 50 sx.	etails, and give pertinent dates, including the state of used 8 5/8"-28#	casing at 330° with
Spud Aug. 13, 175 sx "c" + 2	1975, 11:30 AM. Cemented % c.c. circulated 50 sx.	etails, and give pertinent dates, including the state of used 8 5/8"-28#	casing at 330° with
Spud Aug. 13, 175 sx "c" + 2	1975, 11:30 AM. Cemented % c.c. circulated 50 sx.	etails, and give pertinent dates, including the state of used 8 5/8"-28#	casing at 330° with
Spud Aug. 13, 175 sx "c" + 2	1975, 11:30 AM. Cemented % c.c. circulated 50 sx.	etails, and give pertinent dates, including the state of used 8 5/8"-28#	casing at 330° with
Spud Aug. 13, 175 sx "c" + 2	1975, 11:30 AM. Cemented % c.c. circulated 50 sx.	etails, and give pertinent dates, including the state of used 8 5/8"-28#	casing at 330° with
Spud Aug. 13, 175 sx "c" + 2. Tested 600# fo	1975, 11:30 AM. Cemented % c.c. circulated 50 sx.	etails, and give pertinent dates, including 317° of used 8 5/8"-28# Plug down 7:00 PM. WOC	casing at 330° with
Spud Aug. 13, 175 sx "c" + 2. Tested 600# fo	1975, 11:30 AM. Cemented % c.c. circulated 50 sx.	etails, and give pertinent dates, including 317° of used 8 5/8"-28# Plug down 7:00 PM. WOC	casing at 330° with
Spud Aug. 13, 175 sx "c" + 2. Tested 600# fo	1975, 11:30 AM. Cemented % c.c. circulated 50 sx. r 30". O.K.	etails, and give pertinent dates, including 317° of used 8 5/8"-28# Plug down 7:00 PM. WOC	casing at 330° with
Spud Aug. 13, 175 sx "c" + 2. Tested 600# fo	1975, 11:30 AM. Cemented % c.c. circulated 50 sx. r 30". O.K.	etails, and give pertinent dates, including 317° of used 8 5/8"-28# Plug down 7:00 PM. WOC	casing at 330° with
Spud Aug. 13, 175 sx "c" + 2. Tested 600# fo	1975, 11:30 AM. Cemented % c.c. circulated 50 sx. r 30". O.K.	etails, and give pertinent dates, including 317° of used 8 5/8°-28# Plug down 7:00 PM. WOC	casing at 330° with 18 hours.
Spud Aug. 13, 175 sx "c" + 2 Tested 600# fo	1975, 11:30 AM. Cemented % c.c. circulated 50 sx. r 30". O.K.	etails, and give pertinent dates, including 317' of used 8 5/8"-28# Plug down 7:00 PM. WOC	casing at 330° with 18 hours.
Spud Aug. 13, 175 sx "c" + 2 Tested 600# fo 18. I hereby certify that the information in the information i	1975, 11:30 AM. Cemented % c.c. circulated 50 sx. r 30". O.K.	etails, and give pertinent dates, including 317° of used 8 5/8°-28# Plug down 7:00 PM. WOC	casing at 330° with 18 hours.
Spud Aug. 13, 175 sx "c" + 2 Tested 600# fo	1975, 11:30 AM. Cemented % c.c. circulated 50 sx. r 30". O.K.	etails, and give pertinent dates, including 317' of used 8 5/8"-28# Plug down 7:00 PM. WOC	casing at 330° with 18 hours.