Form 3160-5 (June 1990)			N.M. Oil Cons. Di	Di. On	
	UNITED STATI DEPARTMENT OF THE BUREAU OF LAND MAN	INTERIOR	P.O. Box 1980 Hobbs, NM 88241	FORM APPROVED Budget Bureau No. 1000 0135 Expires: March 31, 1993 5. Lease Designation and Serial No.	
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT" for such proposals			NM-0558018 6. If Indian, Alluttee or Tribe Name		
·····	SUBMIT IN TRIPL	ICATE		7. If Unit or CA, Agreement Designation	
I. Type of Well X. Oil Well Gas Well	Other			8. Well Name and No.	
2. Name of Operator		(505)		- Union SI Federal #1	
3. Address and Telephone No	UM CORPORATION	(505)	748-1471)	9. API Well No.	
105 South 4th St., Artesia, NM 88210				30-005-20490 10. Field and Pool, or Exploratory Area	
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)				Tomahawk San Andr	
660' FNL & 66	0' FWL of Section 1-T8S-	R31E (Unit	D, NWNW)	11. County or Parish, State	
				Chaves Co., NM	
	PPROPRIATE BOX(s) TO IND	ICATE NATU	RE OF NOTICE, REPC	RT, OR OTHER DATA	
	UBMISSION		TYPE OF ACTION		
_ Notice of I	ntent			Change of Plans	
X Subsequen	Denus	Recompleti		New Construction	
	ו אכן אונ	L J Flugging B		L Non Routine Fracturing	
Final Abai	idanment Notice	Altering Ce		Conversion to Injection	
		Other		Dispose Water (Note: Report results of multiple completion on	
4-8-98 - Moved pump. POOH wi	l in and rigged up plugg tth rods and pump. Nipp	ing equipme led down we	ertinent to this work)* ent. Picked up on		
4-8-98 - Moved pump. POOH with tubing. Dig of 4-9-98 - Rigge RIH with tubin anchor. RIH with set $4-1/2$ " CIH sacks Class C 4-10-98 - Nipp up on casing a 4-1/2" casing 4-11-13-98 - Min 4-14-98 - Find Nippled up well from 50' below 4-15-98 - RIH	I in and rigged up plugg th rods and pump. Nipp down cellar. Shut down is ed up wireline. RIH with ag anchor and tubing to 9 with 3-3/4" bit, crossove 3P at 4000'. Pumped 100 cement from 4000-3698'. oled down tubing, BOP and and removed slips. Worke at 3230'. POOH with with No report. Ished POOH with 90 joints the POOH with 90 joints and tagged top of cement	ing equipme led down we for night. h 3-3/4" ga 90' and sta er and cas: bbls mud 1 POOH with d flanged u ed and stre reline. PO s of casing ubing tools ve. Pulled t at 3108'.	entiment to this work)* ent. Picked up on ellhead and nippled acked out. POOH - ing scraper to 4000 laden fluid with no tubing and settin up wellhead. Welde etched casing. RIH DOH with 20 joints g. Nippled down 4- s. Spotted 50 sach d up hole. Shut do . Circulated hole	polish rod and unseat d up BOP. POOH with scale and BS on tubing o'. POOH. RIH and o circulation. Spot 20 ng tool. Shut in. ed on pull sub. Picked d with wireline and cut 4-1/2" casing. Shut i -1/2" casing tools. cs Class "C" 2% CaCl2 own. with mud laden fluid.	
4-8-98 - Moved pump. POOH with tubing. Dig of 4-9-98 - Rigge RIH with tubin anchor. RIH with set $4-1/2$ " CIH sacks Class C 4-10-98 - Nipp up on casing a 4-1/2" casing 4-11-13-98 - N 4-14-98 - Finith Nippled up well from 50' below 4-15-98 - RIH Pulled up hole	I in and rigged up plugg th rods and pump. Nipp down cellar. Shut down ed up wireline. RIH with ag anchor and tubing to 9 with 3-3/4" bit, crossove 3P at 4000'. Pumped 100 cement from 4000-3698'. oled down tubing, BOP and and removed slips. Worke at 3230'. POOH with with to report. Ished POOH with 90 joints lihead, BOP and 2-3/8" to and tagged top of cement e and spot 50 sacks Class d top of cement at 1595'	ing equipme led down we for night. h 3-3/4" ga 90' and sta er and cas: bbls mud 1 POOH with d flanged u ed and stre reline. PO s of casing ubing tools ve. Pulled t at 3108'. s C cement . Pulled u COM	entiment to this work)* ent. Picked up on ellhead and nippled auge ring and stack acked out. POOH - ing scraper to 4000 laden fluid with no tubing and settin up wellhead. Weld etched casing. RIH DOH with 20 joints g. Nippled down 4- s. Spotted 50 sack d up hole. Shut do Circulated hole with 2% CaCl2 at 1 up hole. Spotted 5 VTINUED ON NEXT PAO	polish rod and unseat d up BOP. POOH with scale and BS on tubing o'. POOH. RIH and o circulation. Spot 20 ng tool. Shut in. ed on pull sub. Picked d with wireline and cut 4-1/2" casing tools. sc Class "C" 2% CaCl2 own. with mud laden fluid. 1750'. POOH. WOC. 50 sacks Class C cement	
4-8-98 - Moved pump. POOH wi tubing. Dig of 4-9-98 - Rigge RIH with tubin anchor. RIH w set 4-1/2" CIH sacks Class C 4-10-98 - Nipp up on casing a 4-1/2" casing 4-11-13-98 - N 4-14-98 - Fini Nippled up well from 50' below 4-15-98 - RIH Pulled up hole RIH and tagged	I in and rigged up plugg th rods and pump. Nipp down cellar. Shut down ed up wireline. RIH with ag anchor and tubing to 9 with 3-3/4" bit, crossove BP at 4000'. Pumped 100 cement from 4000-3698'. oled down tubing, BOP and and removed slips. Worke at 3230'. POOH with with to report. Shed POOH with 90 joints liked POOH with 90 joints liked POOH with 90 joints and tagged top of cement e and spot 50 sacks Class d top of cement at 1595'	ing equipme led down we for night. h 3-3/4" ga 90' and sta er and cas: bbls mud 1 POOH with d flanged u ed and stre reline. PO s of casing ubing tools ve. Pulled t at 3108'. s C cement . Pulled u COM	entiment to this work)* ent. Picked up on ellhead and nippled auge ring and stack acked out. POOH - ing scraper to 4000 laden fluid with no tubing and settin up wellhead. Weld etched casing. RIH DOH with 20 joints g. Nippled down 4- s. Spotted 50 sach d up hole. Shut do Circulated hole with 2% CaCl2 at 1 up hole. Spotted 5	polish rod and unseat d up BOP. POOH with sed out at 30'. POOH. scale and BS on tubing o'. POOH. RIH and o circulation. Spot 20 ng tool. Shut in. ed on pull sub. Picked H with wireline and cut 4-1/2" casing tools. sc Class "C" 2% CaCl2 own. with mud laden fluid. 1750'. POOH. WOC. 50 sacks Class C cement	
4-8-98 - Moved pump. POOH with tubing. Dig of 4-9-98 - Rigge RIH with tubin anchor. RIH with set 4-1/2" CIH sacks Class C 4-10-98 - Nipp up on casing a 4-1/2" casing 4-11-13-98 - Nipp up on casing a 4-14-98 - Finit Nippled up web from 50' below 4-15-98 - RIH Pulled up hole RIH and tagged 14 i hereby certify that the for Signed	I in and rigged up plugg th rods and pump. Nipp down cellar. Shut down ed up wireline. RIH with ag anchor and tubing to 9 with 3-3/4" bit, crossove BP at 4000'. Pumped 100 cement from 4000-3698'. oled down tubing, BOP and and removed slips. Worke at 3230'. POOH with with at 3230'. POOH with with to report. Ished POOH with 90 joints the POOH with 90 joints the ADP and 2-3/8" to and tagged top of cemen e and spot 50 sacks Class d top of cement at 1595' megoing is up and correct the office use	ing equipmo led down we for night. h 3-3/4" ga 90' and sta er and cas: bbls mud 1 POOH with d flanged u ed and stre reline. PO s of casing ubing tools ve. Pulled t at 3108'. s C cement . Pulled u CON	entiment to this work)* ent. Picked up on ellhead and nippled auge ring and stack acked out. POOH - ing scraper to 4000 laden fluid with no tubing and settin up wellhead. Weld etched casing. RIH DOH with 20 joints g. Nippled down 4- s. Spotted 50 sack d up hole. Shut do Circulated hole with 2% CaCl2 at 1 up hole. Spotted 5 VTINUED ON NEXT PAO	polish rod and unseat d up BOP. POOH with scale and BS on tubing o'. POOH. RIH and o circulation. Spot 20 ng tool. Shut in. ed on pull sub. Picked d with wireline and cut 4-1/2" casing tools. cs Class "C" 2% CaCl2 own. with mud laden fluid. 1750'. POOH. WOC. 50 sacks Class C cement SE: Date_April 17, 199	
4-8-98 - Moved pump. POOH with tubing. Dig of 4-9-98 - Rigge RIH with tubin anchor. RIH with set 4-1/2" CIH sacks Class C 4-10-98 - Nipp up on casing at 4-1/2" casing 4-11-13-98 - Nipp up on casing at 4-14-98 - Finit Nippled up well from 50' below 4-15-98 - RIH Pulled up hole RIH and tagged 14 i hereby certify that the for Signed - History Conference	I in and rigged up plugg th rods and pump. Nipp down cellar. Shut down ed up wireline. RIH with ag anchor and tubing to 9 with 3-3/4" bit, crossove BP at 4000'. Pumped 100 cement from 4000-3698'. oled down tubing, BOP and and removed slips. Worke at 3230'. POOH with with at 3230'. POOH with with to report. Ished POOH with 90 joints the POOH with 90 joints the ADP and 2-3/8" to and tagged top of cemen e and spot 50 sacks Class d top of cement at 1595' megoing is up and correct the office use	ing equipmo led down we for night. h 3-3/4" ga 90' and sta er and cas: bbls mud 1 POOH with d flanged u ed and stre reline. PO s of casing ubing tools ve. Pulled t at 3108'. s C cement . Pulled u CON ue Operati	entiment to this work)* ent. Picked up on ellhead and nippled auge ring and stack acked out. POOH - ing scraper to 4000 laden fluid with no a tubing and settin up wellhead. Welde etched casing. RIH DOH with 20 joints g. Nippled down 4- s. Spotted 50 sack d up hole. Shut do . Circulated hole with 2% CaCl2 at 1 up hole. Spotted 5 VTINUED ON NEXT PAC	polish rod and unseat d up BOP. POOH with scale and BS on tubing o'. POOH. RIH and o circulation. Spot 20 ng tool. Shut in. ed on pull sub. Picked d with wireline and cut 4-1/2" casing. Shut i -1/2" casing tools. (s Class "C" 2% CaCl2 own. with mud laden fluid. 1750'. POOH. WOC. 50 sacks Class C cement SE: Date _ APR 2.3 199	
4-8-98 - Moved pump. POOH wi tubing. Dig of 4-9-98 - Rigge RIH with tubin anchor. RIH w set 4-1/2" CIH sacks Class C 4-10-98 - Nipp up on casing a 4-1/2" casing 4-11-13-98 - N 4-14-98 - Finit Nippled up well from 50' below 4-15-98 - RIH Pulled up hole RIH and tagged 14 Thereby certify that the fo Signed (This space for Faten of Approved by Conditions of approval, of	I in and rigged up plugg th rods and pump. Nipp lown cellar. Shut down ed up wireline. RIH with ag anchor and tubing to 9 with 3-3/4" bit, crossove 3P at 4000'. Pumped 100 cement from 4000-3698'. oled down tubing, BOP and and removed slips. Worke at 3230'. POOH with with to report. Ished POOH with 90 joints the POOH with 90 joints the ad, BOP and 2-3/8" to v casingg cut to 50' above and tagged top of cemen e and spot 50 sacks Class d top of cement at 1595' regoing is up and correct the office use bide office use bide office use any:	ing equipmo led down we for night. h 3-3/4" ga 90' and sta er and cas: bbls mud 1 POOH with d flanged u ed and stre reline. PO s of casing ubing tools ve. Pulled t at 3108'. s C cement . Pulled u CO ue Operati	entiment to this work)* ent. Picked up on ellhead and nippled auge ring and stack acked out. POOH - ing scraper to 4000 laden fluid with no tubing and settin up wellhead. Welde etched casing. RIH DOH with 20 joints g. Nippled down 4- s. Spotted 50 sack d up hole. Shut do . Circulated hole with 2% CaCl2 at 1 up hole. Spotted 5 VTINUED ON NEXT PAC ons Technician	polish rod and unseat i up BOP. POOH with scale and BS on tubing o'. POOH. RIH and o circulation. Spot 20 ng tool. Shut in. ed on pull sub. Picked i with wireline and cut 4-1/2" casing tools. (s Class "C" 2% CaCl2 own. with mud laden fluid. 1750'. POOH. WOC. 50 sacks Class C cement Date April 17, 199	

mil