

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. K-3189

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator MWJ Producing Company	8. Farm or Lease Name Chaveroo "B" State
3. Address of Operator 413 First National Bank Bldg., Midland, Texas 79701	9. Well No. 1
4. Location of Well UNIT LETTER <u>H</u> , <u>1650</u> FEET FROM THE <u>North</u> LINE AND <u>330</u> FEET FROM THE <u>East</u> LINE, SECTION <u>2</u> TOWNSHIP <u>8S</u> RANGE <u>32E</u> NMPM.	10. Field and Pool, or Wildcat Chaveroo (San Andres)
15. Elevation (Show whether DF, RT, GR, etc.) 4472.6 GL	12. County Chaves

## Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

### NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

### SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled to TD 4355', Ran 109 jts. 4-1/2" 11.6# J-55 ST&C csg. and set at 4355'. Cemented with 225 sxs class C 50/50 pozmix with 2% gel, 5# salt per sx and .4 of 1% CFR-2. Mixed at 14.8# per gal. Plugged down at 5:20 p.m. 11-25-75 WOC 8 hrs.

*min woc 13 hrs*

Ran temperature survey found top cement 3810'.

Released rig.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *John L. Schlager* TITLE AGENT DATE 12/4/75

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

DEC 5 1975

OIL CONSERVATION COM. AM.  
HOBS, N. M.