Form 9-331 Dec. 1973

LINITED STATES

Form A	pproved			
Budget	Bureau	No.	42-R	1424

OMILD STATES	5. LEASE		
DEPARTMENT OF THE INTERIOR	NM-046153-A		
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME		
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir, Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME		
reservoir, Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME		
1. oil gas cher	Miller Federal		
Well General	9. WELL NO.		
2. NAME OF OPERATOR	6		
Amoco Production Company 3. ADDRESS OF OPERATOR	10. FIELD OR WILDCAT NAME Tom-Tom San Andres		
P. O. Box 68 Hobbs, NM 88240			
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA		
AT SURFACE: 660' FSL X 660' FWL, Sec. 34	12. COUNTY OR PARISH 13. STATE		
AT TOP PROD. INTERVAL: (Unit M, SW/4, SW/4)	Chaves NM		
AT TOTAL DEPTH:	14. API NO.		
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,			
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 4294' GL		
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:			
TEST WATER SHUT-OFF			
SHOOT OR ACIDIZE	CEIVED		
REPAIR WELL	(NOTE: Based to the second		
PULL OR ALTER CASING	(NOTE: Report results of multiple completion or zone)		
CHANGE ZONES	. GISAVEV		
ABANDON*	EULUGIJAL SURVEY		
(other) ARTE	SIA, NEW MEXICO		
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is dimeasured and true vertical depths for all markers and zones pertinent	e all pertinent details, and give pertinent dates,		
Propose to increase production by the follow	ing method:		
Run tubing and packer and set packer at 3860 3878'-83' with 1000 gallons 15% LSTNE acid. of fresh water. Swab well. Pull packer and with 4 DJSPF. Run a retrievable bridge plug 3850' and packer at 3810'. Acidize perfs 38 LSTNE acid and flush with 640 gallons of free packer. Run pumping equipment and return we	Flush perfs with 630 gallons perforate casing at 3827'-3837' and packer. Set bridge plug at 27'-3837' with 1500 gallons 15% sh water. Pull bridge plug and		
Subsurface Safety Valve: Manu. and Type	Set @ Ft.		
18. I hereby certify that the foregoing is true and correct SIGNED TITLE ASST. Ad. Ana.	lyst date		
(This space for Federal or State offi			
APPROVED LET'S. BEL) PETER W. CHESTER ITLE CONDITIONS OF APPROVAL IF ANY.			
0+4-USGS, A 1-Hou 1-Susp	1-MKE		