

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. K-2779
7. Unit Agreement Name
8. Farm or Lease Name State 6
9. Well No. 10
10. Field and Pool, or Wildcat Chaveroo-San Andres
12. County Chaves

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-
2. Name of Operator CHAMPLIN PETROLEUM COMPANY
3. Address of Operator 701 Wilco Building - Midland, Texas 79701
4. Location of Well UNIT LETTER J 1980 FEET FROM THE South LINE AND 1980 FEET FROM THE East LINE, SECTION 6 TOWNSHIP 8-S RANGE 33-E NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 4457' GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Sitton & Norton Drilling Company spudded 3:45 P.M/ 7-24-76. Drilled 12-1/4" hole to 1472' and 11" hole to 1937'. Set 8-5/8" 24# @ 1937' and cemented with 650 sxs. Litewate followed by 200 sxs Class "C" w/2% CaCl. Plug down @ 1:45 A.M. W.O.C. 18 hrs. Tested BOP & casing to 800# for 30". Tested O.K. Drilled 7-7/8" hole to 4500'. Set 4-1/2" 10.5# Casing @ 4500' and cemented with 250 sxs. 50-50 POZMIX "B" w/2% Gel & 8# salt/sack. Plug down @ 1:00 P.M. 8-2-76. WOC 91 hrs. Top of cement 3450'. Perforated San Andres @ 4231, 4233, 4235, 4239, 4248, 4250, 4252, 4259, 4261, 4263, 4266, 4271, 4274, 4281, 4285, 4289, 4292, 4301, 4304, 4306, 4309, 4312, 4316, 4318, 4320, 4322, 4324, 4326, 4329, & 4331' (30 holes). Treated perms w/3000 Gals. 15% DS-30 Acid. Swabbed tested well. Fractured well w/50,000 Gals. Gelled KCl Water & 70,000# 20-40 Sand. Swabbed tested well. Ran Tubing & Rods w/Pump for completion.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Isabel M. Randolph TITLE District Clerk DATE August 24, 1976

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: