

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	
Fee	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator Harvey E. Yates Company, Inc.		8. Farm or Lease Name Graves
3. Address of Operator Suite 1000 Security Nat'l Bank Bldg., Roswell, New Mexico 88201		9. Well No. 2
4. Location of Well UNIT LETTER <u>K</u> <u>1980</u> FEET FROM THE <u>South</u> LINE AND <u>1980</u> FEET FROM THE <u>West</u> LINE, SECTION <u>6</u> TOWNSHIP <u>8S</u> RANGE <u>31E</u> NMPM.		10. Field and Pool, or Wildcat Siete-San Andres
15. Elevation (Show whether DF, RT, GR, etc.) 4194.6 GR		12. County Chaves

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <u>Perforate & acidize</u> <input checked="" type="checkbox"/>

16. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work, SEE RULE 1103.

10/26/76 Perforations 3602-06-08, 3664-68-73-76-78-88, 3719-29-30-31. 1 shot/ft, total 13 perfs.

Broke down perfs with 750 gal 15% HCL acid in 3 - 250 gal stages. Acidized casing perforations 3602-3732, 13 holes with 5000 gal. 20% HCL acid in 20 stages on 1 RCN ball/5½ barrels acid. Total 20 ball sealers.

10/27/76 Swab test

10/28/76 Ran tubing and rods, pump setting depth 3594'.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Harvey E. Yates TITLE Vice President DATE 11/11/76

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

NOV 13 1976

OIL CONSERVATION COMM.
ROBBS, N. M.