

COPIES RECEIVED		
DISTRIBUTION		
DATE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
K-3351	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator Champlin Petroleum Company		8. Farm or Lease Name State 5-8-33
3. Address of Operator 300 Wilco Building Midland, Texas 79701		9. Well No. 10
4. Location of Well UNIT LETTER <u>I</u> , <u>1980</u> FEET FROM THE <u>South</u> LINE AND <u>660</u> FEET FROM THE <u>East</u> LINE, SECTION <u>5</u> TOWNSHIP <u>8-S</u> RANGE <u>33-E</u> NMPM.		10. Field and Pool, or Wildcat Chaveroo-San Andres
15. Elevation (Show whether DF, RT, GR, etc.)		12. County Chaves

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Sitton Drilling Company spudded 1:00 P.M. 9-13-76. Drilled 12½" hole to 1320' & 11" hole to 1940'. Set 8-5/8" 24# @ 1938' and cemented w/650 sacks litewate followed by 200 sacks Class "C" w/2% CaCl. Plug down @ 8:00 P.M. 9-15-76. WOC 18 hours. Tested BOP and casing to 800# for 30 minutes. Tested OK. Drilled 7-7/8" hole to 4450'. Set 4½" 10.5# casing @ 4448' and cemented w/250 sacks 50-50 pozmix w/2% gel, 8# salt/sack and ½# flocele/sack. WOC 86 hours. Tested casing to 1000# for 30 minutes. Tested OK. Perforated San Andres @ 4221, 4239, 4242, 4248, 4256, 4264, 4266, 4268, 4270, 4311, 4316, 4318, 4320, 4326, 4328, 4330, 4337, 4339, 4341, 4343, 4346 & 4361. (22 holes) Treated perfs w/3500 gals. 15% DS-30 acid. Swabbed tested well. Fractured perfs w/50,000 gals. gelled KCL water & 70,000# 20-40 sand. Swabbed tested well. Ran tubing and rods w/pump for completion.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Walter M. Anderson TITLE District Clerk DATE October 11, 1976

APPROVED BY _____ TITLE _____ DATE OCT 14 1976

CONDITIONS OF APPROVAL, IF ANY: