NO. OF COPIES RECEIVED		
	-	Form C-103 Supersedes Old
DISTRIBUTION		C-102 and C-103
SANTAFE	NEW MEXICO OIL CONSERVATION COMMISSION	Effective 1-1-65
FILE	_	
U.S.G.S.	_	Sa. Indicate Type of Lease
LAND OFFICE	_	State Fee. X
OPERATOR		5. State Oil & Gas Lease No.
		-
(DO NOT USE THIS FORM FOR P USE "APPLICA	RY NOTICES AND REPORTS ON WELLS ROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. ATION FOR PERMIT - " (FORM C-101) FOR SUCH PROPOSALS.)	
1.		7. Unit Agreement Name
OIL GAS WELL WELL	-	
2. Name of Operator	8. Farm or Lease Name	
Flag-Redfern Oil C	Southard 26	
3. Address of Operator		9. Well No.
P.O. Box 23, Midla	nd, Texas 79702	1
4. Location of Well		10. Field and Pool, or Wildoat
UNIT LETTERD	660 FEET FROM THE NORTH LINE AND 660 FI	Undesignated
THE West LINE, SECT	10N 26 TOWNSHIP 7-S RANGE 31-E	NMPM.
	15. Elevation (Show whether DF, RT, GR, etc.)	
	12. County	
16.	4376 G.L.	Chaves
Check	Appropriate Box To Indicate Nature of Notice, Report	or Other Data
NOTICE OF I	QUENT REPORT OF:	
·		
PERFORM REMEDIAL WORK	PLUG AND ABANDON REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON	COMMENCE DRILLING OPNS.	PLUG AND ABANDONMENT
PULL OR ALTER CASING	CHANGE PLANS X CASING TEST AND CEMENT JOB	
	OTHER	
OTHER		
<ol> <li>Describe Proposed or Completed O work) SEE RULE 1103.</li> </ol>	operations (Clearly state all pertinent details, and give pertinent dates, i	ncluding estimated date of starting any proposed
Flag-Kedtern (	Oil Company desires to change the casing and	cement program for

this new well. Company desires to change the casing and cement program for Change From:

Size of Hole Si 12½"	8-5/8"	Weight per Foot 24# J-55			Estimated Top
		24# T-55	1001		
7 7/01		24# 0 JJ	400'	250 sxs	Circulate
7-7/8"	$4\frac{1}{2}$ "	9.50# J-55	4100'	250 sxs	3000'
Stage Cementer			2050'	650 sxs	Circulate
To:					
Size of Hole Si	ize of Casing	Weight per foot	Setting Depth	Sacks of Cement	Estimated Top
12½"	8-5/8"	24# J-55	1675'	775 sxs	Circulate
7-7/8"	4 <sup>1</sup> <sub>2</sub> "	9.50# J-55	4100'	250 sxs	3000'
			•		

Estimated top of Rustler Anhydrite = 1656'. Cement 8-5/8" casing with 575 sxs of Halliburton lt.wt. with 8 lb.salt per sx followed by 200 sxs of Class "C" with 2%cacl

16. I hereby certify that	at the information above is true and co:	mplete to the best of my knowledge and belief.	
SIGNED	to Grean		DATE April 7, 1973
	Orig. Signed <b>by</b> Jerry Sexten		
CONDITIONS OF APP	Dist I, Suge	TITLE	