## NMOCC COPY

UNITED STATES DEPARTMENT

STATES SUBMIT IN TRIPLICATE.

THE INTERIOR (Other Instructions of the verse side.)

SHOOTING OR ACIDIZING

(Other)

Form approved. Budget Bureau No. 42-R1424. 5. I PASE DESIGNATION AND SERIAL NO.

NM 15892 6. IF INDIAN, ALLOTTEE OR TRIBE NAME

ABANDONMENT

GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to addirect regrow E

	Use "APPLICATION FOR PERMIT—" for such proposals.)			<b>*</b>	
1.	OIL X GAS OTHER	UG 31	1979	7. UNIT AGREEMENT NA	ME
2.	NAME OF OPERATOR			8. FARM OR LEASE NAM	E
	Blair Exploration Inc. & Thomas R. Metcalfe	O. C.	C.	Hudson Feder	
3.	ADDRESS OF OPERATOR	TEBIA, D	FFICE	9. WELL NO.	.41
	308 HBF Building, Midland, Texas 79701			/	
4.	OCATION OF WELL (Report location clearly and in accordance with any State requirements.* ee also space 17 below.) t surface			10. FIELD AND POOL, OR WILDCAT	
	660'FSL & 660' FEL Unit "P"			Wildcat	
				11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA	
				Sec. 7, T7S-	R31 E
14.	PERMIT NO.   15. ELEVATIONS (Show whether DF, RT, GR, etc.)				
				12. COUNTY OR PARISH	13. STATE
	4322 GL			Chaves	NM
6.	Check Appropriate Box To Indicate Nature of N	otice, Re	port, or O	ther Data	
	NOTICE OF INTENTION TO			ENT REPORT OF:	
	. [				
	TEST WATER SHUT-OFF PULL OR ALTER CASING WATE	R SHUT-OFF	ı	REPAIRING W	ELL
	FRACTURE TREAT MULTIPLE COMPLETE FRACT	URE TREATM	MENT	ALTERING CAS	SING
	SHOOT OR ACIDIZE ABANDON* SHOO	TING OR ACT	012180		-  - <del></del>

- (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*
  - Run tbg. to 4800' and circulate hole with 10# mud laden fluid using 25 sacks of salt gel with 100 bbls. of brine water.
  - Spotted a 25 sack plug at 4800' and tagged plug at 3550'. 2.

CHANGE PLANS

REPAIR WELL

(Other)

- Shot 4-1/2" csg. at 1700' pulled & layed down 4-1/2" csg. 3.
- Run tbg. to 1750' and pump & spot a 25 sack plug from 1750' to 1650'. 4.
- Pulled tbg. to 1400' & spotted a 30 sack plug from 1400' to 1300'. 5.
- Pulled tbg. to 450' & spotted a 30 sack plug from 450' to 350'. 6.
- POH cut off well head, install Dry Hole marker and surface plug. Rigged down.

## RECEIVED

OCT 27 1977

U.S. GEULUGICAL SURVEY ADTTOLA NO

	IN, NEW MEXICO		
18. I hereby certify that the foregoing is true and correct	TITLE PHA Cont.	DATE 10-4-77	
(This space for Federal or State office use)			
APPROVED BY OF SIDE ALBERT R. STALL CONDITIONS OF APPROVAL, IF ANY:	TITLE ACTING DISTRICT ENGINEER	DATEAUG 3 0 1979	

Reserve Andrews Control of the Contr

O. O. O. ARTESIA, OFFICE

0CT 21 1977

SEP 1 n 1979

RECEIVED

RECEIVED

O.C.D. HOBBS, OFFICE