Form: 3160-5 /November 1983) (Formerly 9-331)

## UNITED STATES N. M. GIL CONS. CO.MISSION UNITED STATES N. M. GIL CONS. CO.MISSION DEPARTMEN OF THE INTERIOR POPULATION OF THE I

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

Formerly 9-331) BUREAU OF LAND MANAGEMEN HOBBS, NEW MEXICO LEASE DESIGNATION AND SERIAL NO. 88240 NM-0354427-A 6. IF INDIAN, ALLOTTEE OR TRIBE NAME SUNDRY NOTICES AND REPORTS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.

Use "APPLICATION FOR PERMIT—" for such proposals.) 7. UNIT AGREEMENT NAME 2 15 PM '91 WELL X WELL OTHER NAME OF OPERATOR S. FARM OR LEASE NAME BUREA U MGT ROSWELL RESOURCE Amoco Federal Yates Energy Corporation
3. ADDRESS OF OPERATOR AREA 9. WELL NO. P. O. Box 2323, Roswell, New Mexico 88202-2323 LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\* See also space 17 below )
At surface 10. FIELD AND POOL, OR WILDCAT Cato San Andres 11. SEC., T., E., M., OR BLE. AND SURVEY OR AREA 1980' FNL & 660' FEL Section 1-8S-30E 14. PERMIT NO. 30-005-20588 15. ELEVATIONS (Show whether DF, RT, GR, etc.) 12. COUNTY OF PARISH 13. STATE NM 3800' KB Chaves 16 Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSECUENT REPORT OF : TEST WATER SHUT-OFF PULL OR ALTER CASING REPAIRING WELL FRACTURE TREATMENT ALTERING CASING SHOOT OF ACIDIZE X SHOOTING OR ACIDIZING ABANDONMENT\* REPAIR WELL CHANGE PLANS (NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) (Other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state al. pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\* Propose to plug and abandon well as follows: Install a 4 1/2" CIBP @ 3500'. 2. Dump 35 sx. cement on CIBP. Cut csg. off at approx. 1800'. Place a 25 sx. cmt. plug 50' inside csg. stub and another 50' out of csg. stub. 35 sx. cmt. plug 328'-228'.

6. 15 sx. cmt. plug @ surface.

7. Install dry hole marker.

18

I hereby certify that the foregoing is true and correct	Ortice Landman	DATE 3-13-91
(This space for Federal or State office use)		
APPROVED BYCONDITIONS OF APPROVAL, IF ANY:	TITLE	DATE