

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other ☐
well well
2. NAME OF OPERATOR
Shell Oil Company
3. ADDRESS OF OPERATOR
P.O. Box 1509, Midland, Texas 79702
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 660' FNL & 660' FWL
AT TOP PROD. INTERVAL: Same
AT TOTAL DEPTH: Same
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☒
(other)

SUBSEQUENT REPORT OF:

- ☐
☐
☐
☐
☐
☐
☐
☐
☐

5. LEASE

NM-0155254A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Amco A Federal

9. WELL NO.

6

10. FIELD OR WILDCAT NAME

Cato (San Andres)

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Section 4, T-9-S, R-30-E

12. COUNTY OR PARISH

Chaves

13. STATE

New Mexico

14. API NO.

NA

15. ELEVATIONS (SHOW DF, KDB, AND WD)
4127.7' Gr.

RECEIVED

(NOTE: Report results of multiple completion or zone change on Form 9-331)

JUN 6 1979

U.S. GEOLOGICAL SURVEY
ARTERIA

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Pull prod equipment
2. Spot 30 sx cmt @ TD (est 290' of fill for 30 sx cmt).
3. Fill the hole w/salt gel mud consisting of 10# brine W/25# of gel/bbl.
4. Spot 20 sx cmt above top of salt @ 1040' (est 190' of fill for 20 sx cmt in 5 1/2" csg).
5. Spot 20 sx cmt from 310' upward. Top of cmt must be 50' up from btm of 8 5/8" csg (est 195' of fill for 20 sx cmt in 5 1/2" csg).
6. Spot cmt in 5 1/2" @ surf from btm of cellar down 20'.
7. Mark location w/4" OD steel pipe @ least 4' above GL w/"Amco Federal A No. 6, Sec. 4-9S-30E" welded on pipe.
8. Clean location.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED G.W. Tullos TITLE Senior Prod. Eng. DATE 6-04-79

(This space for Federal or State office use)

APPROVED BY (Ord. Sec.) ALBERT R. STALL TITLE ACTING DISTRICT ENGINEER DATE JUL 24 1979

CONDITIONS OF APPROVAL, IF ANY:

Subject to conditions of plugging approval dated June 8, 1979.

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between, and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.