

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYForm approved.
Budget Bureau No. 42 R1424.
5. LEASE DESIGNATION AND SERIAL NO.

NM 0347394

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

East Tom Tom

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Undesignated

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 6-8S-32E

Unit B NMPM

12. COUNTY OR PARISH

Chaves

13. STATE

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☐ GAS WELL ☐ OTHER ☐

DRY

2. NAME OF OPERATOR

Yates Petroleum Corporation

3. ADDRESS OF OPERATOR

207 South 4th Street - Artesia, NM 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

660' FNL & 1980' FEL of Section 6-8S-32E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4491' KB; 4480' GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☒(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 4400'; PBTD 4355'. Well Plugged and Abandoned as follows: Cut off casing at 2875'. Filled hole with heavy mud. Set Cast Iron Bridge Plug at 4080' and dumped 2 bailers of cement on top of plug. Set 35 sack cement plug at 2881-2780' across the 4½" stub. Set 35 sack cement plug 1762-1660' across 8-5/8" casing - could not tag cement plug at 1762'. Re-spotted 50 sacks of Neat Cement at 1762'. WOC, tagged cement plug, and held OK. Spotted 8 sacks of cement at surface. Heavy mud placed between each plug. A dry hole marker will be installed. Job Completed at 9:00 AM 9-26-77.

The location will be cleaned, pits filled and fenced if needed, surface restored in accordance w/agreement with the surface owner.

18. I hereby certify that the foregoing is true and correct

SIGNED

Christina Lomelua

TITLE

Geol. Secty.

DATE

9-30-77

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

APPROVED
PETER W. CHESTER

AUG 5 1986

BUREAU OF LAND MANAGEMENT
ROSWELL RESOURCE AREA

*See Instructions on Reverse Side