Form 9-331 (May 1962)	UNITER TATES	SUBMIT IN TRIPLICAT (Other instructions on verse side)	TO O. C. C. Form approved. Budget Bureau No. 4 5. LEASE DESIGNATION AND SEE		
	GEOLOGICAL SURVEY Y NOTICES AND REPORTS ON		NM 0347394 6. IF INDIAN, ALLOTTEE OR TEN	BE NAME	
	for proposals to drill or to deepen or plug back "APPLICATION FOR PERMIT-" for such propos	to a different reservoir. als.)			
I. OIL CAS WELL OTHER Dry			7. UNIT AGREEMENT NAME		
2. NAME OF OPERATOR			S. FARM OR LEASE NAME	S. FARM OR LEASE NAME	
Yates Petroleum Corporation 3. ADDRESS OF OPERATOR			East Tom Tom		
207 South 4th Street - Artesia NM 88210			9. WEIL NO.	1	
207 South 4th Street - Artesia, NM 88210 4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)			10. FIELD AND POOL, OR WILDC.	AT	
At surface			Undesignated	-	
660' FNL & 1980' FEL of Section 6-88-32E			11. SE2., T., R., M., OR BLE. AND SURVEY OR AREA SEC. 6-85-32E		
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT,	GR. etc.)	Unit B 12. COUNTY OB PARISH 13. ST		
	4480'GR - 4491'			M	
16.	Check Appropriate Ray To Indiana No.				
	Check Appropriate Box To Indicate Natur				
Г		SUBSE	QUENT REPORT OF:		
TEST WATER SHUT-OFF FRACTURE TREAT	PULL OR ALTER CASING	WATER SHUT-OFF	REPAIRING WELL		
SHOOT OR ACIDIZE	MULTIPLE COMPLETE	FRACTURE TREATMENT	ALTERING CASING		
REPAIR WELL	CHANGE PLANS	SHOOTING OR ACIDIZING [ABANDONMENT*		
(Other)		(NOTE : Report result	ts of multiple completion on Well pletion Report and Log form.)]	
17. DESCRIPE PROPOSED OR COM proposed work. If well nent to this work.)*	PLETED OPERATIONS (Clearly state all pertinent det is directionally drilled, give subsurface locations	ails, and give pertinent dates and measured and true verti	s, including estimated date of sta- cal depths for all markers and zo	rting any nes perti-	
······································	ested Non-commercial and				
l Will s	set Cast Iron Bridge Plug	at 4080' and d	r an the well a	S IOLLO	
of BP.	We will notify USGS in	Hobbs when n	lugging will be d	t on to	
2 Will s	shoot off casing at 2390'	and fill hole	with mud	one.	
3 Will s	set 35 sacks of cement plu	ug across 41/	stub		
4 Will r	oull $4\frac{1}{2}$ " casing and set 3	5 sacks cement	nlug at 1770 167	01	
across	the 8-5/8" casing shoe	- shoe is at 1	י סבע מנ 1//V-10/ סבי	0.	
5 Will s	set 10' cement plug at su	rface and erect	125. r dru holo mulau		
6 Will c	lean up location, fence	nits until dry	then lovel and	•	
surfac	e to satisfaction of the	surface owner	Mary Terring of	restore	
Roswel	.1, New Mexico.	Surface Owner,	, Mays Jenkins of		
	The Mexico.				
18. I hereby certify that the	foregoing is true and correct				
SIGNED - Cotil		ineer	EATE 9-7-77		
(This space for Federal o	r State office use)	APPRE AS AME	IVED		
APPROVED BY	TITLE	APPRL	NDEN		
CONDITIONS OF APPRO	VAL, IF ANY :	AS AME	1077 - 170		
	*0 .	D D DEI	BROWN		
	*See Instructions on	Reverse pide ARTHUR	R. BROWN TENGINEER		
		DISTRIC			