CHANGE PLANS (Other) Spud (Note: Rep Completion		(Note: Report result	results of multiple completion on Well Recompletion Report and Log form.)		
FRACTURE TREAT BHOOT OR ACIDIZE	MULTIPLE COMPLETE ABANDON*	FRACTURE TREATMENT SHOOTING OR ACIDIZING	ALTERING CA	T*	
TEST WATER SHUT-OFF	PULL OR ALTER CASING	WATER SHUT-OFF			
NOTICE OF INTENTION TO:			SUBSEQUENT REPORT OF:		
16. Check	Appropriate Box To Indicate	Nature of Notice, Report, or G	Other Data		
14. PERMIT NO.	15. ELEVATIONS (Show whether 4479.	B7 GR	Chaves	13. STATE NM	
		•	Sec. 6-8S-32		
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 660 FNL and 1980 FEL of Section 6-T8S-R32E			10. FIELD AND POOL, OR WILDCAT 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA		
3. ADDRESS OF OPERATOR 207 South 4th Street - Artesia, NM 88210			9. WELL NO.		
Yates Petroleum Corporation			East Tom Tom		
1. OIL X GAS WELL X OTHER 2. NAME OF OPERATOR			7. UNIT AGREEMENT NA:		
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)			6. IF INDIAN, ALLOTTEE	OR TRIBE NAME	
DEPARTMENT OF THE INTERIOR verse side) GEOLOGICAL SURVEY		Budget Bureau No. 42-R1424. 5. LEASE DESIGNATION AND SERIAL NO. NM 0347394 6. IF INDIAN, ALLOTTEE OR TRIBE NAME			

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded a $12\frac{1}{4}$ " hole at 10:00 AM 7-7-77.

TD 1725'- Ran 43 joints of 8-5/8" 24# J-55 casing (1725') set at 1725'. 1-Guide Shoe, Centralizers at 1685 and 1660'. Cemented w/610 sacks of 50-50 poz + 3% CaCl tailed in w/150 sacks of Class C + 2% CaCl. PD 5:15 AM 7-10-77. Cement circulated 35 sacks to surface. WOC 18 hours. NU installed BOP's and tested to 1500#. OK. Reduced hole to 7-7/8", drilled plug and tested to 600#. OK. Resumed drilling.

18. I hereby certify that the foregoing is true and correct SIGNED (7-19-3 7
(This space for Federal or State office use)	ACCEPTED FOR RECORD
APPROVED BY TITLE CONDITIONS OF APPROVAL, IF ANY:	JUL 1977
*See Instructions on Reverse Side	U. S. GEOLOGICAL SURVEY HOBBS, NEW MEXICO