UNIT STATES UNIT STATES SUBMIT IN TRIPLICATES (Other instructions of verse side)

Form approved, Budget Bureau No. 42-R1424. 5. LEASE DESIGNATION AND SERIAL NO.

NM-15895 6. IF INDIAN, ALLOTTER OR TRIBE NAME

GEOLOGICAL SURVEY				
SUNDRY NOTICES				

SUNDRY NC (Do not use this form for pro Use "APPLI	DTICES AND REPORTS ON WELLS posals to drill or to deepen or plug back to a different reservoir. (CATION FOR PERMIT—" for such proposals.)		
OIL GAS X OTHER		7. UNIT AGREEMENT NA	
2. NAME OF OPERATOR Maralo, Inc.		8. FARM OR LEASE MAN	1
3. ADDRESS OF OPERATOR P. O. Box 832.	Midland, Texas 79702	9. WELL MO. 1 10. FIELD AND POOL, OF	WILDCAT
4. LOCATION OF WELL (Report location See also space 17 below.) At surface	n clearly and in accordance with any State requirements.*	Wildcat	
660' FSL & 1980)' FWL Sec. 3 Unit N	Sec. 3, T-	
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 4293 GR	Chaves	N.M.
16. Chack	Appropriate Box To Indicate Nature of Notice, Report, o	r Other Data	. •

	Check	Appropriate box to t	udicate 14	igiture of inotice, Report, or Oil	6. Dail
NOTI	CE OF I	NTENTION TO:		RUBERGURN	r asport of:
TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL (Other)		PULL OR ALTER CASING MULTIPLE COMPLETE ABANDON* CHANGE PLANS	<u>X</u>	WATER SHUT-OFF FRACTURE TREATMENT SHOOTING OR ACIDIZING (Other) (Note: Report results of Completion or Recompletic	REPAIRING WELL ALTERING CABING ABANDONMENT® multiple completion on Well on Report and Log form.)
				dates inc	duding estimated data of starting

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and some pertinent to this work.) *

Drilled well to total depth of 10,305'; Did not encounter productive zones. Ran electrical logs prior to requesting verbal approval to P&A.

Proposed plugging procedures:

50 sx 150' from 9750 - 9600' Class H Cement 50 sx 150' from 8000 - 7850' Class H Cement 40 sx 100' from 6060 - 5960' Class H Cement 40 sx 100' from 4600 - 4500' Class H Cement 40 sx 100' from 3530 - 3430' Class H Cement 15 sx 20' to surface.

Fluid between cement plugs 9.9# drilling mud.

Plugs to be spotted to drill pipe.

R. L. BEEKMAN ACTING DISTRICT ENGINEER RECEIVED
AUG 2 1977 U.S. GEOLOGICAL SURVEY NEW MEXICO

18. I hereby certify that the foregoing in true and correct signed	TITLE Production Clerk	DATE August 1, 1977
(This space for Federal or State office use) A D CONDITIONS OF APPROVAL, IF ANY:	TITLE	DATE
AUG 4 - 1977		

*See Instructions on Keverse Dide

CIL CONSERVATION COMMEN

AUG S 1977
AUG S 1977