			C. OOM		-			
Form 9-331 (May 1963)	UNITED STATES SUB DEPARTMENT OF THE INTERIOR Version			UBMIT IN TRIPLICATI Other instructions on p erse side)	DLICATE* Form approved. Budget Bureau No. 42-R1424. 5. LEASE DESIGNATION AND SERIAL NO.			
	G	GEOLOGICAL SURVEY			NM-5492			
	this form for proposa	CES AND REPOR	r plug back to	a different reservoir.			OR TRIBE NAME	
	AS DOTHER	Dry Hole			7. UNIT A	GREEMENT NAD	ME	
2. NAME OF OPERATOR						8. FARM OR LEASE NAME		
McClellan Oil Corporation						Kcorpac		
3. ADDRESS OF OPP	RATOR			· · · · · · · · · · · · · · · · · · ·	9. WELL I	NO.		
Box 848, Roswell, New Mexico 88201						2		
BOX 848, ROSWEII, New Mexico 88201 4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements in the surface RECEIVED At surface RECEIVED					10. FIELD	10. FIELD AND POOL, OR WILDCAT Wildcat		
	990' FSL 8	& 330' FEL		DEC 4 1978	Sec.1	T., R., M., OR BI RVBY OR AREA		
14. PERMIT NO.		15. ELEVATIONS (Show who	ether DF, RT, GR	"BEULUGICAL SURVE	Y   12. COUNT	TY OR PARISH	13. STATE	
		4467'GL	A	TESIA, NEW MEXICO	Chav	/es	New Mexico	
16.	Check Ap	propriate Box To India				L		
NOTICE OF INTENTION TO: SUBSEQU						ENT REPORT OF:		
TEST WATER S	HUT-OFF P	ULL OR ALTER CASING	]	WATER SHUT-OFF		REPAIRING W	ELL	
FRACTURE TREA	AT X	IULTIPLE COMPLETE		FRACTURE TREATMENT		ALTERING CA	SING	
SHOOT OR ACID	IZE A	BANDON*	_	SHOOTING OR ACIDIZING		ABANDONMEN	т• Х	
REPAIR WELL	c	HANGE PLANS		(Other)				
(Other)				(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)				
17. DESCRIBE PROPO proposed won nent to this w	rk. If well is direction	RATIONS (Clearly state all p nally drilled, give subsurfa	pertinent detail ace locations an	s, and give pertinent dat d measured and true ver	es, including e fical depths fo	stimated date r all markers	of starting any and zones perti-	

AL 1.

On November 27 & 28, 1978, freed  $4\frac{1}{2}$ " casing at 1000'. Loaded hole w/heavy mud. Spotted 50' cement plug 3050-3097', Pumped 35 sx plug 1050', Top of plug 945' after two hours. Pumped 50 sx plug at 400'. Set 10 sx plug at surface and installed dry hole marker. Will restore surface as near as possible to it's original condition (Fee Surface). Recovered 1000' of  $4\frac{1}{2}$ " casing.

18. I hereby certify that the foregoing is true and correct SIGNED J. M. Collan	TITLEOperator	DATE _	11/30/78
(This space for Federal or State office use) APPROVED BY (Citig. Sol.) ALBERT R. STALL CONDITIONS OF APPROVAL, IF ANY:	TITLE ACTING DISTRICT ENGINEER	DATE _	JAN+2 5 1980

\*See Instructions on Reverse Side

RECEIVED

JAN 29 1980

O. C. D. ARTESIA, OFFICE

RECEIVED JAN 31 1980 OIL CONSERVATION DIV.