

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator MWJ Producing Company		8. Farm or Lease Name Mobil-Graves
3. Address of Operator 413 First National Bank Building, Midland, Texas 79701		9. Well No. 1
4. Location of Well UNIT LETTER C 660 FEET FROM THE North LINE AND 2180 FEET FROM West THE LINE, SECTION 7 TOWNSHIP 8-S RANGE 31-E NMPM.		10. Field and Pool, or Wildcat Cato
15. Elevation (Show whether DF, RT, GR, etc.) 4208.6 Ground		12. County Chaves

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐  
OTHER ☐

PLUG AND ABANDON ☐  
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐  
COMMENCE DRILLING OPNS. ☐  
CASING TEST AND CEMENT JOBS ☐  
OTHER ☐  
ALTERING CASING ☐  
PLUG AND ABANDONMENT ☒

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

11/28/78 MI Unit.

11/29/78 Rig up and pulled 111 jts. tbg. Laid down Seating Nipple and packer. Ran 4 1/2" bridge plug and set at 3600'. Pumped 35' (5 sacks) cement on top. Cut 4 1/2" casing at 2884'. Pulled and laid down 35 joints casing. Shut down for night.

11/30/78 Laid down additional 50 jts. 4 1/2" casing a total of 2884'. Rigged up and ran 89 jts. of 2 3/8" tbg. (2934'). Spotted 40 sack plug and pulled out. Waited 2 hours and tagged cement plug with wire line at 2740'. Ran Baker Model K cement retainer; set at 1340'. Pumped 50 sack plug. Pulled out of retainer; pulled and laid down 41 jts. tbg.

12/1/78 Pumped 10 sack plug in top of 8 5/8" casing and installed marker. Well P & A.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED R. B. Meach TITLE Agent DATE 12/1/78

APPROVED BY A. G. [Signature] TITLE Oil & Gas Conservation DATE 12/1/78

CONDITIONS OF APPROVAL, IF ANY: