

NMOCC COPY
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER		7. UNIT AGREEMENT NAME	
2. NAME OF OPERATOR DEPCO, Inc.		8. FARM OR LEASE NAME Sundance Federal	
3. ADDRESS OF OPERATOR 800 Central, Odessa, Texas 79761		9. WELL NO. 1	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1980' FS & EL, Sec. 3, T12S, R30E, Unit Letter J		10. FIELD AND POOL, OR WILDCAT Wildcat	
14. PERMIT NO.		15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3971.1	
		12. COUNTY OR PARISH Chaves N.	13. STATE N. M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETION ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐
REPAIR WELL ☐	CHANGE PLANS ☐
(Other) ☐	

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒	REPAIRING WELL ☐
FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
(Other) ☐	

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 4-24-78 Spud 9:15 AM. Drilled 17 1/2" hole to 300'. Ran 8 jts. 13 3/8" 48# H-40 casing set @ 300'. Cemented w/325 sx. Class "C" w/2% ca. cl., 1/4# Cello Flakes and 5# Gilsomite, Cement circulated. WOC. 19 hrs. Put on BOP and tested casing 1000# for 30 min. OK.
- 4-28-78 Drilled 11" hole to 2804'. Ran 12 jts. (463') 8 5/8" 32#, 59 jts. (1974') 24#, 9 jts. (367') 32# casing set at 2804'. Cemented w/800 sx. Class "C", 2% lodense, 2% ca. cl., 1/4# Cello Flakes, 800# salt. Followed w/200 sx. Class "C" w/2% cal cl. Top of cement 1310'. WOC 18 hrs. Tested casing 1000# for 30 min. Held OK.

RECEIVED

MAY 26 1978

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED D. R. Mason TITLE Chief Clerk DATE 5-25-78

(This space for Federal or State office use)

APPROVED BY [Signature] TITLE ACTING DISTRICT ENGINEER DATE MAY 30 1978

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1953-O-685229

867-651

RECEIVED
JUN - 1 1978
O.C.C.
ARTERIAL OFFICE

RECEIVED

878-5070

U.S. GOVERNMENT PRINTING OFFICE