

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

**OIL CONSERVATION DIVISION**  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

|   |
|---|
| WELL API NO.<br>30-005-20631  |
| 5. Indicate Type of Lease<br>STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/> |
| 6. State Oil & Gas Lease No.<br>-   |

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:  
OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. Name of Operator  
Yates Drilling Company

3. Address of Operator  
105 South 4th Street, Artesia, NM 88210

4. Well Location  
Unit Letter K : 1980 Feet From The South Line and 1730 Feet From The West Line  
Section 3 Township 13S Range 31E NMPM Chaves County

7. Lease Name or Unit Agreement Name  
Phyllis

8. Well No.  
2

9. Pool name or Wildcat  
SE Chaves On Gas Area Assoc.

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

**NOTICE OF INTENTION TO:**

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐  
OTHER: ☐

**SUBSEQUENT REPORT OF:**

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☒  
CASING TEST AND CEMENT JOB ☐  
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

11-5-93 RUPU

11-6-93 TOH with tubing. TIH with Halliburton Cement Retainer. Pumped thru retainer and set retainer at 2505'. Squeezed perms. 2740'-44' with 35 sxs. Premium Plus Neat Cement. Dumped 100' cement on top of retainer. Set 25 sxs. Premium Plus cement plug from 2130'-1890'. Set 25 sxs. Premium Plus Cement plug from 1169'-929'. Set 25 sxs. cement plug from 607'-367'. Set 15 sxs. cement plug from 100' to surface. Removed wellhead and installed dry hole marker. All equipment removed and location ready for inspection.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

*John Rhodes*

TITLE Petroleum Engineer

DATE 11-19-93

TYPE OR PRINT NAME

TELEPHONE NO.

(This space for State Use)

APPROVED BY

*Jack Griffin*

TITLE

**OIL & GAS INSPECTOR**

DATE DEC 15 1993

CONDITIONS OF APPROVAL, IF ANY: