

NMOCC COPY
UNIT STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

NM-15015-A
6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

RECEIVED

2. NAME OF OPERATOR
SUNDANCE OIL COMPANY

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

3. ADDRESS OF OPERATOR
Suite 510, 1776 Lincoln St., Denver, CO 80203

MAY 15 1978

Oakason Federal

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

O. G. G.
ARTESIA, OFFICE

9. WELL NO.

3

10. FIELD AND POOL, OR WILDCAT

Tom Tom San Andres

660' FSL, 660' FWL

Unit M

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Section 33-T7S-R31E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4278.4 GL

12. COUNTY OR PARISH 13. STATE

Chaves

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

SET SURFACE CASING

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

XXX

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

Spudded 12 1/4" surface hole 4/26/78. Drilled to 1503'. Ran 38 jts., 23 & 24#, 8 5/8" surface casing to 1500'. Cemented w/500 sx Class C mixed w/2% CaCl. Circulated 50 sx. Pressured up to 800#, held OK. WOC 12 hrs. Prior to drilling out tested BOP to 800 psi, OK.

RECEIVED
MAY 10 1978
U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Richard O. Dimit

TITLE Vice President, Production

DATE May 8, 1978

(This space for Federal or State office use)

APPROVED BY

ACTING DISTRICT ENGINEER

TITLE

DATE

MAY 12 1978

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

NOV 18 1978

OIL CONSERVATION COMM.
DURHAM, N. H.