

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" FORM C-101 FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Flag-Redfern Oil Company	8. From or Lease Name Southard 26
3. Address of Operator P.O. Box 23 Midland, TX 79702	9. Well No. 2
4. Location of Well UNIT LETTER <u>E</u> <u>1980</u> FEET FROM THE <u>North</u> LINE AND <u>660</u> FEET FROM THE <u>West</u> LINE, SECTION <u>26</u> TOWNSHIP <u>7-S</u> RANGE <u>31-E</u> N.M.P.M.	10. Field and Pool, or Wildcat Tom-Tom (San Andres)
15. Elevation (Show whether DF, RT, GR, etc.) 4366 GL	12. County Chaves

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled 12-1/4" hole to 1680'.

Ran 39 jts. (1665') of 8-5/8" 8 Rd. 24# J-55 STC casing and set @ 1680'. Cemented w/550 sx. Halliburton light, 1/4# flocele, 8# salt, followed by 200 sx. C1 & 2% CaCl. Circ. 25 sx. to surface. PD @ 7:00 PM 11-5-78. Tested casing to 1500 PSIG. Held OK.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Judy Benton</u>	TITLE <u>Production Clerk</u>	DATE <u>11-8-78</u>
ORIG. SIGNED BY <u>Jerry Sexton</u>	TITLE <u>Dist 1, Supv.</u>	DATE <u>NOV 13 1978</u>
CONDITIONS OF APPROVAL, IF ANY:		