NO. OF COPIES RECEIVED	Form C-103	
DISTRIBUTION	Supersedes Old	
SANTA FE NEW MEXICO OIL CONSERVATION CON	C-102 and C-103	
FILE	MISSION Effective 1-1-65	
U.S.G.S.	Sa. Indicate Type of Lease	
LAND OFFICE	State y Fee	
OPERATOR	5. State Oil & Gas Lease No.	
	LG-9	
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT -" (FORM C-101) FOR SUCH PROPOSALS.)	T RESERVOIR.	
1. OIL GAS OTHER- Dry ON 10 10 10 10 10 10 10 10 10 10 10 10 10	7. Unit Agreement Name	
2. Name of Operator John L. Cox	8. Form or Lease Name State "32"	
3. Address of Operator Box 2217, Midland, Texas 79702	9. Well No.	
4. Location of Well	10. Field and Pool, or Wildcat	
UNIT LETTER P 660 FEET FROM THE East LINE AND	660 FEET FROM Wildcat	
THE SOUTH LINE, SECTION 32 TOWNSHIP 10S RANGE 3	E	
15. Elevation (Show whether DF, RT, GR, etc.,	12. County	
4498 Gr.	Chaves	
Check Appropriate Box To Indicate Nature of Notice	e, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK	ALTERING CASING	
TEMPORARILY ABANDON COMMENCE DRILL	ING OPHS. PLUG AND ABANDONMENT	
PULL OR ALTER CASING CASING TEST AND	CEMENT JQB	
OTHER		
OTHER		
17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed		
the perturbation of the perturbation of the perturbation detects, and give perturbations	nent dates, including estimated date of starting any proposed	
worky see note 1100.		
Plugging procedure as per verbal approval of Mr. John H		
Plugging procedure as per verbal approval of Mr. John Plugging operations begun November 16, 1978.		
Plugging procedure as per verbal approval of Mr. John Plugging operations begun November 16, 1978. Spotted CIBP @ 9000' w/35 sx. cement on top of plug.		
Plugging procedure as per verbal approval of Mr. John Plugging operations begun November 16, 1978. Spotted CIBP @ 9000' w/35 sx. cement on top of plug. Spotted 35 sx. cement plug @ 4777'.		
Plugging procedure as per verbal approval of Mr. John H Plugging operations begun November 16, 1978. Spotted CIBP @ 9000' w/35 sx. cement on top of plug. Spotted 35 sx. cement plug @ 4777'. Recovered 4758' of 4½" casing (4490' left in hole).	unyan 11-13-78.	
Plugging procedure as per verbal approval of Mr. John H Plugging operations begun November 16, 1978. Spotted CIBP @ 9000' w/35 sx. cement on top of plug. Spotted 35 sx. cement plug @ 4777'. Recovered 4758' of 4½' casing (4490' left in hole). Spotted 45 sx. cement plug @ 4000'. (4350' of 8 5/8" ca	unyan 11-13-78.	
Plugging procedure as per verbal approval of Mr. John F Plugging operations begun November 16, 1978. Spotted CIBP @ 9000' w/35 sx. cement on top of plug. Spotted 35 sx. cement plug @ 4777'. Recovered 4758' of 4½" casing (4490' left in hole). Spotted 45 sx. cement plug @ 4000'. (4350' of 8 5/8" caspotted 40 sx. cement plug @ 1600' (363' of 12 3/4" caspotted 40 sx. cement plug @ 1600' (363' of 12 3/4" caspotted 40 sx. cement plug @ 1600'	sing left in hole) sing left in hole)	
Plugging procedure as per verbal approval of Mr. John F Plugging operations begun November 16, 1978. Spotted CIBP @ 9000' w/35 sx. cement on top of plug. Spotted 35 sx. cement plug @ 4777'. Recovered 4758' of 4½" casing (4490' left in hole). Spotted 45 sx. cement plug @ 4000'. (4350' of 8 5/8" caspotted 40 sx. cement plug @ 1600' (363' of 12 3/4" caspotted 10 sx. cement plug @ surface w/dry hole marker.	sing left in hole) sing left in hole)	
Plugging procedure as per verbal approval of Mr. John F Plugging operations begun November 16, 1978. Spotted CIBP @ 9000' w/35 sx. cement on top of plug. Spotted 35 sx. cement plug @ 4777'. Recovered 4758' of 4½" casing (4490' left in hole). Spotted 45 sx. cement plug @ 4000'. (4350' of 8 5/8" cas Spotted 40 sx. cement plug @ 1600' (363' of 12 3/4" cas Spotted 10 sx. cement plug @ surface w/dry hole marker. Hole filled with mud laden fluid.	sing left in hole) sing left in hole)	
Plugging procedure as per verbal approval of Mr. John F Plugging operations begun November 16, 1978. Spotted CIBP @ 9000' w/35 sx. cement on top of plug. Spotted 35 sx. cement plug @ 4777'. Recovered 4758' of 4½" casing (4490' left in hole). Spotted 45 sx. cement plug @ 4000'. (4350' of 8 5/8" caspotted 40 sx. cement plug @ 1600' (363' of 12 3/4" caspotted 10 sx. cement plug @ surface w/dry hole marker.	sing left in hole) sing left in hole)	
Plugging procedure as per verbal approval of Mr. John F Plugging operations begun November 16, 1978. Spotted CIBP @ 9000' w/35 sx. cement on top of plug. Spotted 35 sx. cement plug @ 4777'. Recovered 4758' of 4½" casing (4490' left in hole). Spotted 45 sx. cement plug @ 4000'. (4350' of 8 5/8" cas Spotted 40 sx. cement plug @ 1600' (363' of 12 3/4" cas Spotted 10 sx. cement plug @ surface w/dry hole marker. Hole filled with mud laden fluid.	sing left in hole) sing left in hole)	
Plugging procedure as per verbal approval of Mr. John F Plugging operations begun November 16, 1978. Spotted CIBP @ 9000' w/35 sx. cement on top of plug. Spotted 35 sx. cement plug @ 4777'. Recovered 4758' of 4½" casing (4490' left in hole). Spotted 45 sx. cement plug @ 4000'. (4350' of 8 5/8" cas Spotted 40 sx. cement plug @ 1600' (363' of 12 3/4" cas Spotted 10 sx. cement plug @ surface w/dry hole marker. Hole filled with mud laden fluid.	sing left in hole) sing left in hole)	
Plugging procedure as per verbal approval of Mr. John F Plugging operations begun November 16, 1978. Spotted CIBP @ 9000' w/35 sx. cement on top of plug. Spotted 35 sx. cement plug @ 4777'. Recovered 4758' of 4½" casing (4490' left in hole). Spotted 45 sx. cement plug @ 4000'. (4350' of 8 5/8" cas Spotted 40 sx. cement plug @ 1600' (363' of 12 3/4" cas Spotted 10 sx. cement plug @ surface w/dry hole marker. Hole filled with mud laden fluid.	sing left in hole) sing left in hole)	
Plugging procedure as per verbal approval of Mr. John F Plugging operations begun November 16, 1978. Spotted CIBP @ 9000' w/35 sx. cement on top of plug. Spotted 35 sx. cement plug @ 4777'. Recovered 4758' of 4½" casing (4490' left in hole). Spotted 45 sx. cement plug @ 4000'. (4350' of 8 5/8" cas Spotted 40 sx. cement plug @ 1600' (363' of 12 3/4" cas Spotted 10 sx. cement plug @ surface w/dry hole marker. Hole filled with mud laden fluid.	sing left in hole) sing left in hole)	
Plugging procedure as per verbal approval of Mr. John F Plugging operations begun November 16, 1978. Spotted CIBP @ 9000' w/35 sx. cement on top of plug. Spotted 35 sx. cement plug @ 4777'. Recovered 4758' of 4½" casing (4490' left in hole). Spotted 45 sx. cement plug @ 4000'. (4350' of 8 5/8" cas Spotted 40 sx. cement plug @ 1600' (363' of 12 3/4" cas Spotted 10 sx. cement plug @ surface w/dry hole marker. Hole filled with mud laden fluid.	sing left in hole) sing left in hole)	

	•		
18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.			
SIGNED Manta Frederice	TITLE Production Clerk	DATE 12-22-78	
APPROVED BY David R Catanock CONDITIONS OF APPROVAL, IF ANY:	TITLE OIL & GAS INSPECTOR	DATE AUG 15 1983	