

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. UNIT AGREEMENT NAME ---	
2. NAME OF OPERATOR Flag-Redfern Oil Company		8. FARM OR LEASE NAME Amoco-Federal	
3. ADDRESS OF OPERATOR P.O. Box 23 Midland, TX 79702		9. WELL NO. 4	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 660' FWL & 1980' FSL		10. FIELD AND POOL, OR WILDCAT Tom Tom (San Andres)	
14. PERMIT NO. --		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 26, T-7-S, R-31-E	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 4367 GL		12. COUNTY OR PARISH Chaves	
		13. STATE NM	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
(Other) ☐

PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
ABANDON* ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐
FRACTURE TREATMENT ☐
SHOOTING OR ACIDIZING ☐
(Other) run casing & test ☐
REPAIRING WELL ☐
ALTERING CASING ☐
ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

9-17-78 Drilled 11" hole to 1690'. Ran 40 jts. (1677') of 8-5/8" 24#/ft. K-55 ST&C casing and set @ 1690'. Cmt w/550 sx. Halliburton lite, 1/4# Flocele, 8# salt followed by 200 sx. Cl "C", 2% CaCl. Circulated 75 sx. to surface. WOC 12 hrs. Tested casing to 1000 PSIG-Held OK.

9-23-78 Drilled 7-7/8" hole to 4105'. Ran Sidewall Neutron Porosity log. Ran 105 jts. 4-1/2", 9.5#, J-55, ST&C casing and set @ 4104'. Cmt'd w/250 sx. 50-50 Cl H Pozmix, 2% gel, 8# salt, 0.75% CFR-2. WOC 12 hrs. Tested 4-1/2" casing to 1500 PSIG. Held OK.

RECEIVED
NOV 28 1978
U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED Quay Benton

TITLE Production Clerk

DATE 11-27-78

(This space for Federal or State office use)

FOR Dist. ALBERT R. STALL

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE ACTING DISTRICT ENGINEER

DATE DEC 01 1978