

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Form Approved.  
Budget Bureau No. 42-R1424

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well ☐ gas well ☐ other
2. NAME OF OPERATOR  
SUNDANCE OIL COMPANY
3. ADDRESS OF OPERATOR  
Suite 510, 1776 Lincoln St., Denver, CO 80203
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 2080' FNL, 660' FWL Unit E  
AT TOP PROD. INTERVAL: Same  
AT TOTAL DEPTH: Same
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input type="checkbox"/>	<input type="checkbox"/>
(other) <u>SET SURFACE CASING</u>	

5. LEASE <u>NM-15015-B</u>	
6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
7. UNIT AGREEMENT NAME	
8. FARM OR LEASE NAME <u>Oakason "B" Federal</u>	
9. WELL NO. <u>2</u>	
10. FIELD OR WILDCAT NAME <u>Tom Tom, San Andres</u>	
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA <u>Section 33, T.7S., R.31E.</u>	
12. COUNTY OR PARISH <u>Chaves</u>	13. STATE <u>New Mexico</u>
14. API NO.	
15. ELEVATIONS (SHOW DF, KDB, AND WD) <u>4284' GL, 4296' KB</u>	

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spud at 1:30 p.m. 11/12/78. Drilled 12 1/4" hole to 1015'. Drilled 11" hole from 1015'. Drilled to 1359'. Ran 33 jts. 8 5/8", 22.36# casing. Set at 1359'. Cemented w/175 sx Class C w/3% lowdense followed by 200 sx Class C w/2% CaCl. Plug down at 1 a.m. 11/14/78. Circulated 50 sx cement. Pressured up to 1000# for 30 minutes, okay. WOC.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_

Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Richard O. Dimitt TITLE VP, Production DATE November 14, 1978

APPROVED BY Joe D. Lara ACTING DISTRICT ENGINEER  
CONDITIONS OF APPROVAL, IF ANY: \_\_\_\_\_

NOV 17 1978

RECEIVED

NOV 20 1978

D. C. C.  
ARTESIA, OFFICE

RECEIVED

NOV 22 1978

U.S. CONSERVATION COMM.  
ROBERT, H. M.