

**UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY**

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

JUN 26 19791. oil well ☐ gas well ☒ other ☐2. NAME OF OPERATOR
Exxon Corporation**O. C. C.
ARTESIA, OFFICE**3. ADDRESS OF OPERATOR
P. O. Box 1600, Midland, Texas 797024. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1,980' FWL and 990' FNL of Section
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
 FRACTURE TREAT ☐
 SHOOT OR ACIDIZE ☐
 REPAIR WELL ☐
 PULL OR ALTER CASING ☐
 MULTIPLE COMPLETE ☐
 CHANGE ZONES ☐
 ABANDON* ☐
 (other) ☐

SUBSEQUENT REPORT OF:

☐
☒
☒
☐
☐
☐
☐
☐

RECEIVED

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

JUN 19 1979**U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO**

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 6-5-79 Sec BP @ 9200', pumped 30' of sand on top. PB TD 9170'. Set packer @ 8750' Perforated Strawn w/1 9/16" Select - Fire @ 8787, 88, 89, 90, 91, 92, 93, 94, 95, 96, 97, 98, 99, 8800-01 with 15 shots. Broke down Perfs w/4 BW. Broke @ 2900#. Pump rate 1/2 BPM Avg. Pr. 1600. Final 1700. ISIP 1550. After 10 mins. 975.
- 6-6-79 Swabbed. Acidized 8787-8801 w/2000 gals., 15% HCL.
- 6-8-79 Set, BP @ 4200, dumped 30' sand on top. PBD 4170. Perfed 5 1/2" casing w/1 9/16" Omega jet gun 4000-4006 w/1 shot per ft.
- 6-9-79 Acidized w/1000 gals. 7 1/2 % MFR-100 w/10 gal. A-200 Inhibitor & 5# J-1 Fric. Red. Form broke at 3750 psi. Max 4500# avg. treating Pr. 3700' Instant SI Pr 2800#. 5 min. 2750#. 15 min. 2700#. Swbd.
- 6-14-79 Plugging to abandon.

Subsurface Safety Valve: Manu. and Type

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Melva Kripling TITLE Proration Specialist DATE 6-15-79

(This space for Federal or State office use)

APPROVED BY AGillham TITLE ACTING DISTRICT ENGINEER

CONDITIONS OF APPROVAL, IF ANY:

JUN 25 1979