

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLI
(Other instructions
verse side)U.S.
reForm approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-8945

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

DeSmet-Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 28-9S-30E

12. COUNTY OR PARISH

Chaves

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☐ GAS WELL ☐ OTHER Dry Hole

2. NAME OF OPERATOR

BEARD OIL COMPANY

3. ADDRESS OF OPERATOR

2000 Classen Center, Suite 200 So., Okla. City, OK 73106

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface

1980' FSL & 1980' FEL (NW SE) Sec. 28-9S-30E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4057' GL; 4072' DF; 4074' KB

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐
☐

PULL OR ALTER CASING

☐
☐
☒
☐
☐

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

WATER SHUT-OFF

☐
☐
☐
☐
☐

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

☐
☐
☐
☐
☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Well was drilled to a total depth of 9900'. 13-3/8" casing was set @ 362' with 450 sacks of Class "C" cmt w/2% CaCl. 8-5/8" Intermediate casing was set @ 2800' and cemented with 1200 sacks (950 sx 50/50 Pozmix + 250 sx Class "C" w/2% CaCl). Cement was circulated. Four Drill Stem Tests were run (See Form 9-330 for results of DST's). No commercial shows were encountered. It is proposed to set the following cement plugs at the below listed approximate depths:

No. Sacks

Interval

55

9620-9670'

55

8090-7940

55

6510-6360

35

4800-4700

50

3640-3490

30

2860-2750 (In and out of 8-5/8" intermediate)

25

To of 8-5/8" Intermediate

A regulation dry hole marker will be placed on the well.

RECEIVED

MAY 3 1979

U.S. GEOLOGICAL SURVEY

ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

James W. Vater, Jr.

TITLE Vice President

DATE May 1, 1979

(This space for Federal or State office use)

APPROVED BY

Lee D. Latta

TITLE

ACTING DISTRICT ENGINEER

DATE

MAY 4 - 1979

CONDITIONS OF APPROVAL, IF ANY:

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963-O-685229

847 - 485

RECEIVED

MAY 7 1979

O. C. C.
ARTEBIA, OFFICE