IN. M. O. C. C. COPY

. ...

يونيه مورية

		Form Budge _ت		iu No. 42-R	142
UNITED STATES	5. LEASE		<u> </u>	672	
DEPARTMENT OF THE INTERIOR	NM-15015-B		<u>ب</u>	। এই ছায়ু ।	
GEOLOGICAL SURVEY	6. IF INDIAN	, ALLOTTEE	OR TR		Ξ
		<u></u>	<u></u>	् रुंच	
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGR		AME	.Lo Shirt La	
Do not use this form for proposals to drill or to deepen or plug back to a different servoir. Use Form 9–331–C for such proposals.)	8. FARM OR	LEASE NAM	IF S		
1. oil gas	Oakason "B			to too s abbi ingio	
well well other	9. WELL NO.	101 1 101 1 102 1 102 1	-	្តុំស្នុងទ ទំព័រ សាស្ត្	
2. NAME OF OPERATOR SUNDANCE OIL COMPANY	3	<u> </u>			
3. ADDRESS OF OPERATOR	Tom Tom, S			ក្រុង ឆ្នាំ សូម ឆ្នាំ សូម ឆ្នាំ	
#510, 1776 Lincoln St., Denver, CO 80203	11. SEC., T., F			^ C	v c
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA	: 같은 신간	12	= :3 5	
below.) AT SURFACE: 660' FNL, 1980' FWL, Unit C	Section 33				
AT TOP PROD. INTERVAL:	12. COUNTY C			TATE	
AT TOTAL DEPTH: Same	<u>Chaves</u> 14. API NO.	<u>- 한왕위</u> - 화제공동	New	<u>Mexico</u>	_
5. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,			¥-17	ay or avus 115 v	
REPORT, OR OTHER DATA	15. ELEVATIO	NS (SHOW	DF, K		W
EQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	<u>4301'GL</u>			58.6 L	_
EST WATER SHUT-OFF			.,		
		전문문문	, , ,		
HOOT OR ACIDIZE			2		
	(NOTE: Report change	results of mu		mpletion of	r zo
	i i i i i i i i i i i i i i i i i i i	5 2 2 4 5 2 2 4 5 2 2 4			
HANGE ZONES					
			÷		
BANDON*					
ther) SET SURFACE CASING				son llew a native ta native	
 BANDON* bther) SET SURFACE CASING 7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statistic) including estimated date of starting any proposed work. If well is comeasured and true vertical depths for all markers and zones pertinents 	directionally drille	etails, and d, give subs	give p surface	ertinent d	late s ai
 SET SURFACE CASING DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly staticular including estimated date of starting any proposed work. If well is comeasured and true vertical depths for all markers and zones pertined 	directionally drille nt to this work.)*	d, give sub	surface	locations	lati
 SET SURFACE CASING DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly stating including estimated date of starting any proposed work. If well is comeasured and true vertical depths for all markers and zones pertine Spudded at 10 a.m. 4/11/79. Drilled to 1425 surface casing. Set at 1425'. Cemented wit 	directionally drille nt to this work.)* 5'. Ran 37 ch 200 sacks	d, give subs jts., 8 Class (surface یے 5/8" کہ 3%	, 24#	lati s a
 SET SURFACE CASING DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly stating including estimated date of starting any proposed work. If well is comeasured and true vertical depths for all markers and zones pertine Spudded at 10 a.m. 4/11/79. Drilled to 1425 Surface casing. Set at 1425'. Cemented with 	directionally drille nt to this work.)* 5'. Ran 37 ch 200 sacks	d, give subs jts., 8 Class (surface یے 5/8" کہ 3%	, 24#	s a
 SET SURFACE CASING DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statincluding estimated date of starting any proposed work. If well is comeasured and true vertical depths for all markers and zones pertine Spudded at 10 a.m. 4/11/79. Drilled to 1425 	directionally drille nt to this work.)* 5'. Ran 37 ch 200 sacks	d, give subs jts., 8 Class (surface یے 5/8" کہ 3%	, 24#	lati s a
 SET SURFACE CASING DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly stating including estimated date of starting any proposed work. If well is comeasured and true vertical depths for all markers and zones pertine Spudded at 10 a.m. 4/11/79. Drilled to 1425 Surface casing. Set at 1425'. Cemented with 	directionally drille nt to this work.)* 5'. Ran 37 ch 200 sacks	d, give subs jts., 8 Class (surface یے 5/8" کہ 3%	, 24#	lati s a
 SET SURFACE CASING DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly stating including estimated date of starting any proposed work. If well is comeasured and true vertical depths for all markers and zones pertine Spudded at 10 a.m. 4/11/79. Drilled to 1425 Surface casing. Set at 1425'. Cemented with 	directionally drille nt to this work.)* 5'. Ran 37 ch 200 sacks	d, give subs jts., 8 Class (surface یے 5/8" کہ 3%	, 24#	lati s a
 ther) SET SURFACE CASING DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly stating including estimated date of starting any proposed work. If well is comeasured and true vertical depths for all markers and zones pertine Spudded at 10 a.m. 4/11/79. Drilled to 1425 surface casing. Set at 1425'. Cemented with 	directionally drille nt to this work.)* 5'. Ran 37 ch 200 sacks	d, give subs jts., 8 Class (surface یے 5/8" کہ 3%	, 24#	lati s a
 ther) SET SURFACE CASING DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly stating including estimated date of starting any proposed work. If well is comeasured and true vertical depths for all markers and zones pertine Spudded at 10 a.m. 4/11/79. Drilled to 1425 surface casing. Set at 1425'. Cemented with 	directionally drille nt to this work.)* 5'. Ran 37 ch 200 sacks	d, give subs jts., 8 Class (5/8" 5/8" 2, 3% 4/12	, 24#	lati s a
 ther) SET SURFACE CASING DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly stating including estimated date of starting any proposed work. If well is comeasured and true vertical depths for all markers and zones pertine Spudded at 10 a.m. 4/11/79. Drilled to 1425 surface casing. Set at 1425'. Cemented with 	directionally drille nt to this work.)* 5'. Ran 37 ch 200 sacks	d, give subs jts., 8 Class (5/8" 5/8" 2, 3% 4/12	, 24#	lati s a
 ther) SET SURFACE CASING DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly stating including estimated date of starting any proposed work. If well is comeasured and true vertical depths for all markers and zones pertine Spudded at 10 a.m. 4/11/79. Drilled to 1425 surface casing. Set at 1425'. Cemented with 	directionally drille nt to this work.)* 5'. Ran 37 ch 200 sacks	d, give subs jts., 8 Class (surface یے 5/8" کہ 3%	, 24#	lati s a
 ther) SET SURFACE CASING DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly stating including estimated date of starting any proposed work. If well is comeasured and true vertical depths for all markers and zones pertine Spudded at 10 a.m. 4/11/79. Drilled to 1425 surface casing. Set at 1425'. Cemented with 	directionally drille nt to this work.)* 5'. Ran 37 ch 200 sacks	d, give subs jts., 8 Class (5/8" 5/8" 2, 3% 4/12	, 24#	lati s a
 SET SURFACE CASING DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statincluding estimated date of starting any proposed work. If well is of measured and true vertical depths for all markers and zones pertine. Spudded at 10 a.m. 4/11/79. Drilled to 1425 surface casing. Set at 1425'. Cemented wit followed by 200 sx Class C, 2% CaCl₂. Plug Circulated 50 sx cement. Pressured up to 10 	directionally drille nt to this work.)* 5'. Ran 37 ch 200 sacks	d, give subs jts., 8 Class (5/8" 5/8" 2, 3% 4/12	, 24#	ns
Wher SET SURFACE CASING 7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly stating including estimated date of starting any proposed work. If well is of measured and true vertical depths for all markers and zones pertine. Spudded at 10 a.m. 4/11/79. Drilled to 1425 surface casing. Set at 1425'. Cemented with followed by 200 sx Class C, 2% CaCl ₂ . Plug Circulated 50 sx cement. Pressured up to 10 Ubsurface Safety Valve: Manu. and Type	directionally drille nt to this work.)* 5'. Ran 37 ch 200 sacks	d, give subs jts., 8 Class (5/8" 5/8" 2, 3% 4/12	, 24#	ns
 ther) SET SURFACE CASING 7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statincluding estimated date of starting any proposed work. If well is of measured and true vertical depths for all markers and zones pertine. Spudded at 10 a.m. 4/11/79. Drilled to 1425 surface casing. Set at 1425'. Cemented with followed by 200 sx Class C, 2% CaCl₂. Plug Circulated 50 sx cement. Pressured up to 10 ubsurface Safety Valve: Manu. and Type	directionally drille nt to this work.)* 5'. Ran 37 ch 200 sacks	d, give subs jts., 8 Class (5/8" 5/8" 2, 3% 4/12	, 24#	ns
 SET SURFACE CASING 7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statincluding estimated date of starting any proposed work. If well is of measured and true vertical depths for all markers and zones pertine. Spudded at 10 a.m. 4/11/79. Drilled to 1425 surface casing. Set at 1425'. Cemented wit followed by 200 sx Class C, 2% CaCl₂. Plug Circulated 50 sx cement. Pressured up to 10 Circulated 50 sx cement. Pressured up to 10 ubsurface Safety Valve: Manu. and Type	directionally drille nt to this work.)* 5'. Ran 37 ch 200 sacks down at 10: 000#, held o	d, give subs jts.; 8 Class (55 p.m. kay. W(http://www.second.com/ both April 1	5/8" 5/8" 2, 3% 4/12	, 24#	ns
 wher) SET SURFACE CASING 7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly stating including estimated date of starting any proposed work. If well is of measured and true vertical depths for all markers and zones pertine. Spudded at 10 a.m. 4/11/79. Drilled to 1425 surface casing. Set at 1425'. Cemented with followed by 200 sx Class C, 2% CaCl₂. Plug Circulated 50 sx cement. Pressured up to 100 percenter of the surface Safety Valve: Manu. and Type	directionally drille nt to this work.)* 5'. Ran 37 ch 200 sacks down at 10: 000#, held o 000#, held o	d, give subs jts.; 8 Class (55 p.m. kay. W(http://www.second.com/ both April 1	5/8" 5/8" 2, 3% 4/12	Iocations is locations 24#. 10wde 2/79	ns
SET SURFACE CASING 7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statincluding estimated date of starting any proposed work. If well is of measured and true vertical depths for all markers and zones pertine Spudded at 10 a.m. 4/11/79. Drilled to 1425 Surface casing. Set at 1425'. Cemented with followed by 200 sx Class C, 2% CaCl2. Plug Circulated 50 sx cement. Pressured up to 10 Subsurface Safety Valve: Manu. and Type 8. I hereby certify that the foregoing is true and correct IGNED Molan L. Ashburn (This space for Federal or State of Percoved By Market Ma	directionally drille nt to this work.)* 5'. Ran 37 ch 200 sacks down at 10: 000#, held o	d, give substitutions is a start of the bolt of the bo	5/8" 5/8" 2, 3% 4/12	Iocations in## de la sector de la constant a sector de la constant de la const	ns
wher) SET SURFACE CASING 7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly stating including estimated date of starting any proposed work. If well is of measured and true vertical depths for all markers and zones pertine Spudded at 10 a.m. 4/11/79. Drilled to 1425 Surface casing. Set at 1425'. Cemented with followed by 200 sx Class C, 2% CaCl Plug Circulated 50 sx cement. Pressured up to 10 ubsurface Safety Valve: Manu. and Type	directionally drille nt to this work.)* 5'. Ran 37 ch 200 sacks down at 10: 000#, held o 000#, held o	d, give substitutions is a start of the bolt of the bo	5/8" 5/8" 4/12 00 and angles state administration on a final state of the state of	Iocations in## de la sector de la constant a sector de la constant de la const	ns
wher) SET SURFACE CASING 7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statincluding estimated date of starting any proposed work. If well is of measured and true vertical depths for all markers and zones pertine Spudded at 10 a.m. 4/11/79. Drilled to 1425 Surface casing. Set at 1425'. Cemented with followed by 200 sx Class C, 2% CaCl2. Plug Circulated 50 sx cement. Pressured up to 10 ubsurface Safety Valve: Manu. and Type 8. I hereby certify that the foregoing is true and correct IGNED Molan L. Ashburn (This space for Federal or State of Peproved by 200 state of The State	directionally drille nt to this work.)* 5'. Ran 37 ch 200 sacks down at 10: 000#, held o 000#, held o	d, give subs jts.; 8 Class (55 p.m. kay. W(http://www.second.com/ both April 1	5/8" 5/8" 2, 3% 4/12	Iocations is locations 24#. 10wde 2/79	late s ai

RECEIVED

O. C. C. Artebia, office

ATT - COMPANY