31-105-20695

NO. OF COPIES RECEIVED			5	0 v c	JANCY	
DISTRIBUTION	NEW MEXICO OIL CONSERVATION COMMISSION			orm C-101		
SANTA FE			R	evised 1-1-6	5	
FILE	•		5	A. Indicate	Type of Lease	
U.S.G.S.			1	STATE X	FEE	
LAND OFFICE			. 5	State Oil d	Gas Lease No.	
OPERATOR				K 375	4	
				<u>IIIIII</u>		
APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK						
la, Type of Work					7. Unit Agreement Name	
	DEEPEN					
b. Type of Well		FLUG		8, Farm or Le	ease Name	
OIL X GAS WELL WELL	OTHER	SINGLE MU	ZONE	State	-32	
2. Name of Operator	· · · · · · · · · · · · · · · · · · ·	₩ ² ,		9. Well No.		
MWJ Producing Company					3	
3. Address of Operator					10. Field and Pool, or Wildcat	
1804 First National Bank Building, Midland, Texas 79701					Tom Tom (San Andres)	
	A LOCATED 660		LINE			
		TELT FROM THE <u>FROM CON</u>				
AND 330 FEET FROM THE E	ast LINE OF SEC. 32	TWP. 75 RGE. 31				
			IIIIIA	12. County		
x/////////////////////////////////////				Chaves		
				<u>IIIII</u>		
ΩΙΙΙΙΙΙΙΙΙΙΙΙΙΙΙΙΙΙΙΙΙΙΙΙΙΙΙΙ					///////////////////////////////////////	
19A. Formati				on 20. Rotary or C.T.		
Δ		4000' San Andres		es	Rotary	
21. Elevations (Show whether DF, RT, etc.)	21A. Kind & Status Plug. Bond	21B. Drilling Contractor	· · · · · · ·	22. Approx	. Date Work will start	
-4400' Ground 42.37.5	Blanket-Current	WEK		As <u>soo</u>	n as possible	
23						

PROPOSED CASING AND CEMENT PROGRAM

SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	SACKS OF CEMENT	EST. TOP
12 1/4"	8 5/8"	24#	1450'	700	Circulate
7 7/8"	4 1/2"	9.5#	4.000'	325	2800'
			•		
				1	

Surface casing will be set at top of salt section with cement circulated. Cement for oil string calculated to reach base of salt section.

Double ram BOP to be installed after surface casing cemented, tested to 3,000 psi. and utilized to TD. Rams to be operated daily. Control valve for drill pipe to be available on floor while drilling below surface casing.

APPROVAL STOR FOR SO DAY, STORESS DRILLING COMPLEXED,

20. NOU. EXPIRES -