

Form 9-331
(May 1963)

**UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY**

SUBMIT IN TRIPLICATE
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-8255

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

OCKRELL Federal

9. WELL NO.

10. FIELD AND POOL, OR WILDCAT

WILDCAT

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

SEC 14-T14S-R30E

12. COUNTY OR PARISH

CHAVES

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for proposals.)

MAR 11 1980

**U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO**

1. ☐ OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

PETROLEUM EXPLORATION AND DEVELOPMENT FUNDS, INC.

3. ADDRESS OF OPERATOR

P.O. DRAWER 3547, MIDLAND, TEXAS 79702

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)

See also space 17 below.
At surface

660' FNL & 1980' FWL, SEC. 14-T14S-R30E, CHAVES COUNTY, NEW MEXICO.

APPROX. 20 MILES NE OF LOGO HILLS, NEW MEXICO

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

GR. 3908; DF. 3920; KB 3921

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) **ATTEMPT QUEEN SD. CMP.**

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☒

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) **plug back**

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

☒

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

TD. 11,142

CEMENT PLUGS, WITH DRILLING MUD BETWEEN, SET AS FOLLOWS:

10,846-10,696, 150', 50 SX.

9,661-9,511, 150', 65 SX.

8,166-8,016, 150', 65 SX

6,763-6,613, 150', 125 SX

3,117-3,017, 100', 75 SX

2,575-2,475, 100', 60 SX, SET ACROSS 8 5/8" CSG. SHO. AT 2,526'.

OPERATOR INTENDS TO ATTEMPT COMPLETION AS A QUEEN SAND OIL/GAS WELL AT APPROXIMATELY 2400'-2420'.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

DATE

March 19/1980

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

MAR 11 1980

CONDITIONS OF APPROVAL, IF ANY:

ACTING DISTRICT ENGINEER

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

GPO 680-379

RECEIVED

MAR 12 1980

O. C. D.

TECHNICAL OFFICE