

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐
2. NAME OF OPERATOR
SUNDANCE OIL COMPANY
3. ADDRESS OF OPERATOR
#510, 1776 Lincoln St., Denver, CO 80203
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 330' FNL, 990' FEL, Unit A
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH: Same
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input type="checkbox"/>
(other) SET PRODUCTION CASING	<input type="checkbox"/>	<input type="checkbox"/>

5. LEASE
NM-15678
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Ingram Federal
9. WELL NO.
12
10. FIELD OR WILDCAT NAME
Tom-Tom, San Andres
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
NW NE NE Section 5, T.8S., R.31E.
12. COUNTY OR PARISH
Chaves
13. STATE
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
4264' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled 7 7/8" hole from 1496' to 3996' TD. Ran logs. Ran 101 jts. 4 1/2", 10.5#, J-55 casing. Set at 3996'. Cemented w/300 sx 50/50 Pozmix C w/2% gel, 8# salt, 1/4# cello flakes. Plug down at 7:45 p.m. 11/7/79. Pressured up to 1300#, held okay. PBD 3954'. Rig released at 12 midnight. WOCU.

RECEIVED
NOV 13 1979
U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Richard O. Dimit TITLE Vice President DATE November 8, 1979

(Orig. Sgd.) GEORGE H. STEWART (This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE NOV 13 1979
CONDITIONS OF APPROVAL, IF ANY: _____

11/16/79

RECEIVED

NOV 16 1979

O.C.D.

RECEIVED

NOV 16 1979

O.C.D., HOBBS, OFFICE