RECEIVED

دور میسورد. ورور میسورد ا

 $(-1)^{1/(1-1)}$

· · ·

والمرجوع والمراجع

757

(Orig. Sgd.) GEORGE H. STLW W Space for Federal or State office use)	Form 9-331	NULLC.C.D. NOV 1 3 197		
DEPARTMENT OF THE INTERIORYTEXIA. DFFUE 5. LEAS	Dec. 1973			
GEOLOGICAL SURVEY 6. IF INDIAN, ALLOTTEE OR TRIBE NAME SUNDRY NOTICES AND REPORTS ON WELLS 7. UNIT AGREEMENT NAME De not use find form for proprioting to deepen or plug back to a different 8. FARM OR LEASE NAME 1. oil XI gas other 9. WILL NO. 2. NAME OF OPERATOR 9. WILL NO. 12 3. ADDRESS OF OPERATOR 9. WILL NO. 12 1. oil XI gas GEOLOGICAL SURVEY 9. WILL NO. 3. ADDRESS OF OPERATOR 9. WILL NO. 12 1. OBLOOM WILL (FRONT OR TARDER LOCATION CLEARLY, See space 17. SEC, T. R., M. OR BLK AND SURVEY OF AREA AT TOP PROD. INTERVAL: AT TOP PROD. INTERVAL: 7. WILL NO OR PARISH 13. STATE AT TOP PROD. INTERVAL: Same 14. API NO. 6. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. 18. ELEVATIONS (SHOW DF, KDB, AND WD) 12. OUL OR ALTER CASING 11. STATE 13. STATE 12. OR ALTER CASING 11. CHECK TREES AND ORE SAME 13. STATE 12. OR ALTER CASING 11. STATE 14. API NO. 13. FORT REVEL 11. STATE 13. STATE 14. API NO. 15. ELEVATIONS (SHOW DF, KDB, AND WD) 264' GL 12. OR ALTER CASING 110. STATE CASIN				ં મુદ્
SUNDRY NOTICES AND REPORTS ON WELLS 7. UNIT AGREEMENT NAME De not we high form top preparate to delige or preparate to delige or of deepen or plug back to a different in well XI well or to deepen or plug back to a different in well XI well or to deepen or plug back to a different in well XI well or to deepen or plug back to a different in yell (ARD ARD CALL) 1. oil XI well XI well or to deepen or plug back to a different in well XI well XI well or the well in the				
DB_not_use his form for proposals. To despen or plug back to a different well X1 gas 8. FARM OR LEASE NAME 1. oil well X2 well		GEOLOGICAL SURVEY		RIBE NAME
1. oil well XX gest other 6. PARM OR LEASE NAME 1. oil well XX gest other 9. WELL NO. 2. NAME OF OPERATOR 9. WELL NO. 3. ADDRESS OF OPERATOR 12 10. FIELD OR WILDCAT NAME 10. FIELD OR WILDCAT NAME 7. DADRESS OF OPERATOR 12 11. SCD.T.R. M., OR BLK AND SURVEY OF 10. FIELD OR WILDCAT NAME 7. DADRESS OF OPERATOR 12. 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 N. N. OR BLK AND SURVEY OF AT TOP PRODE INTERVAL: AT TOP PROPORTATE BOX TO INDICATE NATURE OF NOTICE. NEEA AT TOP APPOPRIATE BOX TO INDICATE NATURE OF NOTICE. 13. STATE Chaves IA TOP APPOPRIATE BOX TO INDICATE NATURE OF NOTICE. 14. APP NO. 15. ELEVATIONS (SHOW DF, KDB, AND WD) 4264' GL 14. APP NO. 15. ELEVATIONS (SHOW DF, KDB, AND WD) 14264' GL EQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: 15. ELEVATIONS (SHOW DF, KDB, AND WD) 12. COUNTY OR PARISH ANDROW THE CASING 10. THE COMPLETE 10. FIELD OR WILDCARL APPROVAL TO: 15. ELEVATIONS (SHOW DF, KDB, AND WD) 10. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertiment datas, and give pertiment datas, and give pertiment datas, and give pertiment datas, and cones pertiment to this work.)* <td>(Do not use this fo</td> <td>orm for proposals to drill or to deeper or shut hash to show</td> <td></td> <td></td>	(Do not use this fo	orm for proposals to drill or to deeper or shut hash to show		
well XX weil			-	
2. NAME OF OPERATOR 9. WELL NO. SUNDANCE OIL COMPANY 12 3. ADDRESS OF OPERATOR #510, 1776 Lincoln St., Denver, CO 80203 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below) ISC. T. R. M., OR BLK. AND SURVEY OF AREA AT TOP PROD. INTERVAL: AT TOP PROD. INTERVAL: ISC. T. R. M., OR BLK. AND SURVEY OF AREA AT TOP PROD. INTERVAL: AT TOP PROPRIATE BOX TO INDICATE NATURE OF NOTICE. New Mexico AF SURFACE: ASING CONTOR OF OR ADDRA IS. ELEVATIONS (SHOW DF, KDB, AND WD) 4264' GL IS. ELEVATIONS (SHOW DF, KDB, AND WD) 4264' GL IS. ELEVATIONS (SHOW DF, KDB, AND WD) 4264' GL IS. ELEVATIONS (SHOW DF, KDB, AND WD) 4264' GL IS. ELEVATIONS (SHOW DF, KDB, AND WD) 4264' GL INTURE COMPLETE WILIPLE COMPLETE INTERVENT OF COMPLETE BANDON: Intervesting any proposed work, if well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and Access partiment to this work,''''''''''''''''''''''''''''''''''''	well XX			
SUNDANCE OIL COMPANY 3. ADDRESS OF OPERATOR #510, 1776 Lincoln St., Denver, CO 80203 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below). AT TOP PROD. INTERVAL: AT TOP PROD. INTERVAL: AT TOP PROD. INTERVAL: SUPRACE: 330' FNL, 990' FEL, Unit A AT TOP ADDO. INTERVAL: AT TOTAL DEPTH: Same 6. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA EQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: RACTURE TRAT HANGE ZONE HANGE ZONE BANDON' HANGE ZONE BANDON' BANDON' BANDON' BANDON' BANDON' Spudded 12½" Surface hole at 11 a.m. 10/31/79. Drilled to 1496'. Ran 38 jts Spudded 12½" Surface hole at 1496'. Cemented with 200 sx 3% Lowdense + 200 sy Class C w/2% CaCl_2. Plug down at 6 p.m. 11/1/79. Circulated 25 sx. Pressur to 1000#. Ubsurface Safeby Valve: Manu. and Type Set @	2. NAME OF			
3. ADDRESS OF OPERATOR Time Tom, San Andres #510, 1776 Lincoln St., Denver, CO 80203 11. SEC, T. R., M., OR BLK. AND SURVEY OF AREA below) AT SURFACE: 330' FNL, 990' FEL, Unit A AT TOP FROD, INTERVAL: AT TOP FROD, INTERVAL: AT TOP ADDEPTH: Same 6. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA IS. ELEVATIONS (SHOW DF, KDB, AND WD) EQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: EST WATER SHUT-OFF Image on Form 9-330. MOTO OR ACIDIZE Image on Form 9-330. ULL OR ALTER CASING Image on Form 9-330. MUTHIFLE COMPLETE Image on Form 9-330. ANDON' Image on Form 9-330. Spudded 12¼" Surface hole at 11 a.m. 10/31/79. Drilled to 1496'. Ran 38 jtc Spudded 12¼" surface hole at 110 a.m. 10/31/79. Drilled to 1496'. Ran 38 jtc Spudded 12¼" surface hole at 110 a.m. 11/1/79. Circulated 25 sx. Pressur Not 1000#. Image on form 7. 1979 Image on Form 7. 1979 Class Co w/2% CaCl2. Plug down at 6 p.m. 11/1/79. Circulated 25 sx. Pressur Notes Set @				
#510, 1776 Lincoln St., Denver, C0 80203 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below) II. SEC., T. R., M., OR BLK. AND SURVEY OF AREA M NE NOL INTERVAL: AT TOP PROD. INTERVAL: AT TOTAL DEPTH: Same III. SEC., T. R., M., OR BLK. AND SURVEY OF AREA 6. CHECK APPROPALI TO: SUBSEQUENT REPORT OF. III. SEC., T. R., M., OR BLK. AND SURVEY OF ARETURE TREAT HOOT OR ACIDZE III. SEC., T. R., M., OR BLK. AND SURVEY OF ARETURE TREAT HOOT OR ACIDZE III. SEC., T. R., M., OR BLK. AND SURVEY OF ARETURE TREAT HOOT OR ACIDZE III. SEC., T. R., M., OR BLK. AND SURVEY OF ARETURE TREAT HOOT OR ACIDZE III. SEC., T. R., M., OR BLK. AND SURVEY OF ARETURE TREAT HOOT OR ACIDZE III. SEC., T. R., M., OR BLK. AND SURVEY OF ARETURE TREAT HOOT OR ACIDZE III. SEC., T. R., M., OR BLK. AND SURVEY OF ARETURE TREAT HOOT OR ACIDZE III. SEC., T. R., M., OR BLK. AND SURVEY OF ARETURE TREAT HOOT OR ACIDZE III. SEC., T. R., M., OR BLK. AND SURVEY OF ARETURE TREAT HOOT OR ACIDZE III. SEC., T. R., M., OR BLK. AND SURVEY OF ARETURE TREAT HOOT OR ACIDZE III. SEC., T. R., M., OR BLK. AND SURVEY OF ARETURE TREAT HOOT OR ACIDZE III. SEC., T. R., M., OR BLK. AND SURVEY OF AREA TILL COSING SULL OR ALTER CASING IIII. SEC., T. R., M., OR BLK. AND SURVEY OF AREA				
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AREA M. NE. ME Section 5, T.8S., R.3 IN M. Section 5, T.8S., R.3, ME Section 5, T.8S., R.3, ME Section 1000 J. IN M. Section 5, Section 5, Section 5, Secti	<u>#510, 17</u>	76 Lincoln St., Denver, CO 80203		ND SURVEY OR
AT SUFFACE: 330' FNL, 990' FEL, Unit A AT TOP PROD. INTERVAL: AT TOTA DEPTH: Same 6. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA EQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: EST WATER SHUT-OFF RACTURE TREAT HOOT OR ACIDIZE LEAR WELL ULL OR ALTER CASING ULL OR ALTER CASING TO DECRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work. ⁵ Spudded 12½" surface hole at 11 a.m. 10/31/79. Drilled to 1496'. Ran 38 jts 8 5/8", 24# casing. Set at 1496'. Cemented with 200 sx 3% Lowdense + 200 sy Class C w/2% CaCl ₂ . Plug down at 6 p.m. 11/1/79. Circulated 25 sx. Pressur to 1000#. Ubsurface Safety Valve: Manu, and Type B. Interepreting that the foregeing is true and correct GNE. Licedard O. Dimit. (Onig. Sgd.) GEORGE H. STL: "The space for Federal or State office use) (Onig. Sgd.) GEORGE H. STL: "The space for Federal or State office use) DATE	4. LOCATION	OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA	. **
AT TOP PROD. INTERVAL: AT TOP AD DEPTH: Same 6. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA PEQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: ACTURE TREAT HOOT OR ACIDIZE EPAR WELL ULL OR ALTER CASING ULL OR ALTER CASING DUTIPLE COMPLETE ANAGE ZONES BANDON* ATHER SET SURFACE CASING 7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Spudded 12% " surface hole at 11 a.m. 10/31/79. Drilled to 1496'. Ran 38 jts 8 5/8", 24# casing. Set at 1496'. Cemented with 200 sx 3% Lowdense + 200 sy Class C w/2% CaCl ₂ . Plug down at 6 p.m. 11/1/79. Circulated 25 sx. Pressur to 1000#. Ubsurface Safety Valve: Manu. and Type 8. Intereby Certify that the foregeing is true and correct Charge Safety Valve: Manu. and Type (Orig. Sgd.) GEORGE H STLW (The space for Federal or State office use) (Orig. Sgd.) GEORGE H STLW (THE space for Federal or State office use) ONDITIONS OF APPROVAL IF ANY: DATE DATE (Date Safety Valve: If ANY: DATE DATE (Date Safety Valve: IF ANY: DATE DATE (Date Safety Valve: Manu. HE ANY: DATE DATE DATE (Date Safety Valve: Manu. HE ANY: DATE DATE DATE DATE (Date Safety Valve: Manu. HE ANY: DATE DATE (Date Safety Valve: Manu. HE ANY: (Date Safety Valve: Manu. HE ANY: (Date Safety Valve: Manu.		r: 330' FNL, 990' FFL, Unit A	NW NE NE Section 5,	[.8 ^c ., R.31
14. API NO. 6. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 15. ELEVATIONS (SHOW DF, KDB, AND WD) 4264' GL 16. METCH APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 17. DESCRIBE PROPOSED ON COMPLETE OPERATIONS (Clearly state all pertinent details, and give pertinent details, and give pertinent details, and give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent details, and give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Spudded 12&** surface hole at 11 a.m. 10/31/79. Drilled to 1496'. Ran 38 jts 8 5/8", 24# casing. Set at 1496'. Cemented with 200 sx 3% Lowdense + 200 sy Class C w/2% CaCl ₂ . Plug down at 6 p.m. 11/1/79. Circulated 25 sx. Pressur to 1000#. ubsurface Safety Valve: Manu. and Type Set @ Ft. 8. I hereby certify that the foregeing is true add correct GNED	AT TOP PR	ROD. INTERVAL:		
	AT TOTAL I	DEPTH: Same		V Mexico
15. ELEVATIONS (SHOW DF, KDB, AND WD) 15. ELEVATIONS (SHOW DF, KDB, AND WD) 15. ELEVATIONS (SHOW DF, KDB, AND WD) 16. OT OR ACIDIZE 17. DESCRIBE PROPOSED OR COMPLETE 18. MADON* 19. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 5. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Spudded 12½" Surface hole at 11 a.m. 10/31/79. Drilled to 1496'. Ran 38 jts 8 5/8", 24# casing. Set at 1496'. Cemented with 200 sx 3% Lowdense + 200 sx Class C w/2% CaCl ₂ . Plug down at 6 p.m. 11/1/79. Circulated 25 sx. Pressur to 1000#. ubsurface Safety Valve: Manu. and Type Set @	6. CHECK APP	PROPRIATE BOX TO INDICATE NATURE OF NOTICE,	14. API NO.	
EQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: 4264' GL EST WATER SHUT-OFF	REPORT, O	R OTHER DATA	15. ELEVATIONS (SHOW DF.)	KDB AND WD
EST WATER SHUT-OFF RACTURE TREAT RACIDRE TREAT REPORT RESULTS of multiple completion or zone change on Form 9-330.3 (NOTE: Report results of multiple completion or zone change on Form 9-330.3 (NOTE: Report results of multiple completion or zone change on Form 9-330.3 (NOTE: Report results of multiple completion or zone change on Form 9-330.3 (NOTE: Report results of multiple completion or zone change on Form 9-330.3 (NOTE: Report results of multiple completion or zone change on Form 9-330.3 (NOTE: Report results of multiple completion or zone change on Form 9-330.3 (NOTE: Report results of multiple completion or zone change on Form 9-330.3 (NOTE: Report results of multiple completion or zone change on Form 9-330.3 (NOTE: Report results of multiple completion or zone change on Form 9-330.3 (NOTE: Report results of multiple completion or zone change on Form 9-330.3 (NOTE: Report results of multiple completion or zone change on Form 9-330.3 (NOTE: Report results of multiple completion or zone change on Form 9-330.3 (NOTE: Report results of multiple completion or zone change on Form 9-330.3 (NOTE: Report results of multiple completion or zone change on Form 9-330.3 (NOTE: Report results of multiple completion or zone change on Form 9-330.3 (NOTE: Report results of multiple completion or zone change on Form 9-330.3 (NOTE: Report results of multiple completion or zone change on Form 9-330.3 (NOTE: Report results of multiple completion or zone change on Form 9-330.3 (NOTE: Report results of multiple completion or zone change on Form 9-330.3 (NOTE: Report results of multiple completion or zone change on Form 9-330.3 (NOTE: Report results of multiple completion or zone change on Form 9-330.3 (NOTE: Report results of multiple completion or zone change on Form 9-330.3 (NOTE: Report results of multiple completion or zone change on Form 9-330.3 (NOTE: Report results of multiple change on Form 9-330.3	EQUEST FOR		4264' GL	
RACTURE TREAT HOOT OR ACIDIZE HOOT OR ACIDIZE HOUT OR ALTER CASING ULL OR ALTER CASING ULL OR ALTER CASING HANGE ZONES BANDON* SET SURFACE CASING 7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, and give pertinent dates, and give pertinent dates, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Spudded 12½" surface hole at 11 a.m. 10/31/79. Drilled to 1496'. Ran 38 jts 8 5/8", 24# casing. Set at 1496'. Cemented with 200 sx 3% Lowdense + 200 sy Class C W/2% CaCl ₂ . Plug down at 6 p.m. 11/1/79. Circulated 25 sx. Pressur to 1000#. Ubsurface Safety Valve: Manu. and Type B. I hereby certify that the foregoing is true and correct GNED CHILDER MARKET DATE NOVEMBER 7, 1979 (Orig. Sgd.) GEORGE H. STLX (The space for Federal or State office use) PROVED BY DATE DATE DATE NOVEMBER 7, 1979				
EPAIR WELL (NOTE: Report results of multiple completion or zone change on Form 9-330.) MULTIPLE COMPLETE (NOTE: Report results of multiple completion or zone change on Form 9-330.) T. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Spudded 12½" surface hole at 11 a.m. 10/31/79. Drilled to 1496'. Ran 38 jts: 8 5/8", 24# casing. Set at 1496'. Cemented with 200 sx 3% Lowdense + 200 sy Class C w/2% CaCl ₂ . Plug down at 6 p.m. 11/1/79. Circulated 25 sx. Pressur to 1000#. ubsurface Safety Valve: Manu. and Type Set @				
ULL OR ALTER CASING Image: Completion or zone change on Form 9-330.) (NOTE: Report results of multiple completion or zone change on Form 9-330.) HANGE ZONES Image: Change on Form 9-330.) 7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Spudded 12½" surface hole at 11 a.m. 10/31/79. Drilled to 1496'. Ran 38 jts 8 5/8", 24# casing. Set at 1496'. Cemented with 200 sx 3% Lowdense + 200 sy Class C w/2% CaCl ₂ . Plug down at 6 p.m. 11/1/79. Circulated 25 sx. Pressur to 1000#. ubsurface Safety Valve: Manu. and Type				
ULTIPLE COMPLETE Change on Form 9-330.) HANGE ZONES HANGE ZONES BANDON* Image on Form 9-330.) other) SET SURFACE CASING 7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Spudded 12%" surface hole at 11 a.m. 10/31/79. Drilled to 1496'. Ran 38 jts 8 5/8", 24# casing. Set at 1496'. Cemented with 200 sx 3% Lowdense + 200 sx Class C w/2% CaCl2. Plug down at 6 p.m. 11/1/79. Circulated 25 sx. Pressur to 1000#. B. I hereby Certify that the foregoing is true and correct GNED Mathematic Correct GNED TITLE Vice President NOVember 7, 1979 (Orig. Sgd.) GEORGE H. STLT **** NOTHONS OF APPROVAL IF ANY: TITLE			(NOTE: Report results of multiple of	ompletion or zone
BANDON* Sther) SET SURFACE CASING 7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Spudded 12½" surface hole at 11 a.m. 10/31/79. Drilled to 1496'. Ran 38 jts 8 5/8", 24# casing. Set at 1496'. Cemented with 200 sx 3% Lowdense + 200 sy Class C w/2% CaCl ₂ . Plug down at 6 p.m. 11/1/79. Circulated 25 sx. Pressur to 1000#. Ubsurface Safety Valve: Manu. and Type			change on Form 9-330.)	
SET SURFACE CASING 7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Spudded 12½" surface hole at 11 a.m. 10/31/79. Drilled to 1496'. Ran 38 jts 8 5/8", 24# casing. Set at 1496'. Cemented with 200 sx 3% Lowdense + 200 sx Class C w/2% CaCl ₂ . Plug down at 6 p.m. 11/1/79. Circulated 25 sx. Pressur to 1000#. ubsurface Safety Valve: Manu. and Type Set @			-	
7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Spudded 12½" surface hole at 11 a.m. 10/31/79. Drilled to 1496'. Ran 38 jts 8 5/8", 24# casing. Set at 1496'. Cemented with 200 sx 3% Lowdense + 200 s> Class C w/2% CaCl ₂ . Plug down at 6 p.m. 11/1/79. Circulated 25 sx. Pressur to 1000#. ubsurface Safety Valve: Manu. and Type	(BANDON*			
measured and true vertical depths for all markers and zones pertinent to this work.)* Spudded 12¼" surface hole at 11 a.m. 10/31/79. Drilled to 1496'. Ran 38 jts 8 5/8", 24# casing. Set at 1496'. Cemented with 200 sx 3% Lowdense + 200 s> Class C w/2% CaCl ₂ . Plug down at 6 p.m. 11/1/79. Circulated 25 sx. Pressur to 1000#. bubsurface Safety Valve: Manu. and Type				
B. I hereby certify that the foregoing is true and correct GNED	measured a Spudded 8 5/8", Class C	nd true vertical depths for all markers and zones pertiner 12¼" surface hole at 11 a.m. 10/31/79 24# casing. Set at 1496'. Cemented w/2% CaCl ₂ . Plug down at 6 p.m. 11/2	9. Drilled to 1496'. with 200 sx 3% Lowdens	Ran 38 jts r + 200 sx
B. I hereby certify that the foregoing is true and correct GNED				
B. I hereby certify that the foregoing is true and correct GNED				
B. I hereby certify that the foregoing is true and correct GNED			ter de la companya de	
B. I hereby certify that the foregoing is true and correct GNED				
B. I hereby certify that the foregoing is true and correct GNED				
B. I hereby certify that the foregoing is true and correct GNED				
B. I hereby certify that the foregoing is true and correct GNED				
B. I hereby certify that the foregoing is true and correct GNED	ubcurface Cof-+	Walker Menu and Turn	in the second	
GNED WILL MULL TITLE VICE President DATE November 7, 1979 (Orig. Sgd.) GEORGE H. STLW MILL Space for Federal or State office use) PPROVED BY DATE DATE	/		Set @	Ft.
(Orig. Sgd.) GEORGE H. STLW ME Space for Federal or State office use) PPROVED BY DNDITIONS OF APPROVAL, IF ANY:	8. I hereby cert	handle the of		
(Orig. Sgd.) GEORGE H. SILWAY TAKE DATE DATE DATE	Richard	U. Dimit	DATE November 7,	1979
SNUTTONS OF APPROVAL, IF ANY:	PPROVED BY	.) GEORGE H. SILW WHAN THAN IN THE		
에는 것 같은 것 같	UNDITIONS OF A	FFRUVAL, IF ANY:		
				មិនស្ថារ ស្រុកស្រុក ស្រុក ស ស្រុក ស្រុក ស្រុក ស្រុក ស្រុក ស្រុក ស ស្រុក ស្រុក ស ស ស្រុក ស្រុក ស ស្រុក ស ស ស ស ស ស ស ស ស ស ស ស ស ស ស ស ស ស ស

*See Instructions on Reverse Side