N.M.O.C.D. COPY

.

Form 9–331 Dec. 1973		Form Approved. Budget Bureau No. 42-R1424				
UNITED STATES		5. LEASE			<u>au 110. 42-0.</u>	
DEF	ARTMENT OF THE INTERIOR		16153–A	9. 12		
GEOLOGICAL SURVEY		6. IF INDIA	N, ALLOTTEE	OR TI	RIBE NAME	
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different		7. UNIT AG	REEMENT NA	ME		
reservoir. Use Form 9–3	31-C for such proposals.)	8. FARM O	R LEASE NAM	F		
1. oil gas	s	Western			ederal	' 34
well 🖾 we	li Li other	9. WELL N				
2. NAME OF OPER		1		Ĩ	ಷ್ಟೆ ಕ್ಷ್ಮಿಕ್ಷ	
MORANCO 3. ADDRESS OF OPERATOR			R WILDCAT N	AME		
	Tom-To			<u> </u>		
P. O.	11. SEC., T., AREA	, R., M., OR B	LK. Â	ND SURVEY	' OR	
4. LOCATION OF V below.) 330 '	Section	3/1 11-7	_ C 3	ં ફે સ લોકું • મ ે 2:11	P	
AT SURFACE:	T-7-S, R-31-E, Chaves, NM				R-31-	Ľ
AT TOP PROD.	Chaves		-3 83	NM		
AT TOTAL DEPT	14. API NO.		 2	100	<u> </u>	
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,		_ 30-005	-20708	н т	5 H C H	
REPORT, OR O	THER DATA	15. ELEVATI	ONS (SHOW	DF		WD)
REQUEST FOR APPI	ROVAL TO: SUBSEQUENT REPORT OF:	DF 43	51 <u>2</u> 5± <u>5</u>	130	2222	,
TEST WATER SHUT-OFF			20.2	9 0	110 110 110	
FRACTURE TREAT		fob - ucus orm-	od b	5 4 6 2		
SHOOT OR ACIDIZE REPAIR WELL			iiuo	្លីកន្លែន		
PULL OR ALTER CA		(NOTE: Repo	rt results of mul ge on Form 9-3	tiplac	ompletion or	zone
MULTIPLE COMPLET		Cilan,	ge on Form 9-3	30.)	Line Pol	εv Γ
CHANGE ZONES		, ,		- <u>,</u>	ាម ភូមិនាទ ខ្លាំងទីខ្លាំង	ioi:
ABANDON*	LI LI tion Casing Run Report	Ę	5 4 4 <u>6</u>	e ibal	0 10 10 10 10 10 10	วย
(0	eion eusing kun keport		6 2 3 8 1 7 5 4	2		anoilaurlan
	POSED OR COMPLETED OPERATIONS (Clearly state ated date of starting any proposed work. If well is d rue vertical depths for all markers and zones pertinen			give p urfac	ertinent da e locations	
		-				
9-28-79:	Started 7 7/8" hole at 1668'			0:1	: 2 월 # 3 - 2 월 # 3 - 4 월 6	
10-3-79 :	TD 4130' Ran 113 joints (41		/2" 9 . 5	‡	-55 ST	ъС
	casing & set at 4128'. Ceme	nted wit	h 300	ĸ ₫	0 − 50	
	Pozmix, 8# salt/sx and 1/4#	flocele/	sx. Ĉēa	l cū	lated	
	top of cement at 2900'. Pre	ssure te	sted cas	sing	j_to i	
	1000 psi for 30 minutes. He	ld OK.	a cre suà c suà c cara cra c	5711	_ ≷ ∰ ‴ ÷	
			onat cy of sulv angle c f nu (nu f	31iu	on ou wi couceu a cud tu huế hìn	
			of of a series of a	160	gnithindur tot bs: bis brows: law and instructions conc are shown totion or	
	OCT 9 '	19 79	s bris lis blindis liedto to o Scoto o	ete ano		
	001 0	1010	9.00%55 20%55	52		
	U.S. GEOLOGICA	L SURVEY	ស្រាន មិនសំរុកសំរុក សំរោះទេ សំរោះទេ សំរោះទេ សំរោះទេ សំរោះទេ សំរោះទេស សំរោះទេស សំរោះទេស	ahet2 sule: anoisunteoi	· · · · · · · · · · · · · · · · · · ·	
Subsurface Safety Va	live: Manu. and Type ARTESIA, NEW			0 ¥	ittimdus uct bangi Mal latutoti a con autototutani iacu autototutani iacu	F 4
18. I hereby certify that the foregoing is true and correct			Set @	9 5 5 6 5		. Ft.
SIGNED Jeece T Jewice TITLE Agent			10-04-	-79	1975) 1975) 1975 1975 1975 1975	
(This space for Federal or State office use)				2 42 5 2		
ACTINO DIUTINI ENDINEER						
CONDITIONS OF APPROVAL, IF ANY:						, . .
				n neti Tot	ດາດປະຊຸມ ເຊິ່ງເຊິ່ງ ເຊິ່ງເຊິ່ງເຊິ່ງ ເຊິ່ງເຊິ່ງເຊິ່ງເຊິ່ງເຊິ່ງເຊິ່ງເຊິ່ງເຊິ່ງ	
			ກອງໃ "ເປັນໃນ ກາວ "ກາຍ" ກາວໃຫ້ເປັນ ກາວໃຫ້ເປັນ		2 8 8 0 6 3 9	
			2 응 픽 높	сі. Со		

*See Instructions on Reverse Side