

**N.M.O.C.D. COPY**  
**UNIT STATES**  
**DEPARTMENT OF THE INTERIOR**  
**GEOLOGICAL SURVEY**

SUBMIT IN TRIPLICATE  
(Other instructions on reverse side)

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

N.M. 17227

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

N/A

7. UNIT AGREEMENT NAME

N/A

8. FARM OR LEASE NAME

USA

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

12-14S-30E

12. COUNTY OR PARISH

Chaves

13. STATE

N.M.

1. ☐ OIL WELL ☐ GAS WELL ☒ OTHER Dry hole MAY 22 1980

2. NAME OF OPERATOR  
Dale C. Cheesman, Jr.

3. ADDRESS OF OPERATOR  
1822 Bank of the Southwest Building, Houston, Texas 77002

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)  
At surface 660' from North line & 660' from East line  
12-14S-30E, Chaves County, New Mexico.

14. PERMIT NO.  
Approval 1tr/10-02-79

15. ELEVATIONS (Show whether DF, RT, GR, etc.)  
3,969.2 Ground

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF


PULL OR ALTER CASING

XX

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF


FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*


(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) \*

Reason for abandonment - No shows of oil or gas.

Intend to plug & abandon well according to instructions received from Mr. George Stewart, U.S.G.S., 10-29-79.  
Drilled 12-1/4" surface hole, set 319' of 8-5/8" 20# casing, set with 200 sacks of Class "C" mixed 2% CaCl. Drilled to final T.D. of 2,659'.  
Cement plugs to be placed as follows;  
300 sacks(1,650' - 1,250') Base Salt  
70 sacks(1,020' - 920') Top salt  
70 sacks( 370' - 270')

In and out of surface casing.

3 sacks ( 10' - 0') Cut off casing , cap well and install regulation monument. Well top will be closed with steel plate welded in place.

RECEIVED

JUN 10 1980

O. C. D.  
ARTESIA, OFFICE

18. I hereby certify that the foregoing is true and correct

SIGNED Russell A. Cox TITLE AGENT DATE 10-29-79

(This space for Federal or State office use)

APPROVED BY GEORGE E. STEWART TITLE \_\_\_\_\_ DATE 1980  
CONDITIONS OF APPROVAL, IF ANY: