

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

U.S. DEPT. OF COMMERCE
P. O. BOX 1980
HOBBS, NEW MEXICO 88240

30-0-25-20711
Form Approved.
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐
well well other

2. NAME OF OPERATOR

El Ran, Inc.

3. ADDRESS OF OPERATOR

P.O. Box 911, Lubbock, TX 79408

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: Unit Letter I, 1980' FSL & 1980' FSL

AT TOP PROD. INTERVAL: same

AT TOTAL DEPTH: 4360'

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☒

(other)

SUBSEQUENT REPORT OF:

☐

☐

☐

☐

☐

☐

☐

☐

☒

5. LEASE

NM13999A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Phillips Federal

9. WELL NO.

#2

10. FIELD OR WILDCAT NAME

Chaveroo

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Section 13, T8S, R32E

12. COUNTY OR PARISH

Chaves

13. STATE

N.M.

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
4433' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Set CIBP at 4215' and spot 35' cement plug on top.
2. Run freepoint and cut casing off at 1968' and pulled 4 1/2" casing.
3. Load hole w/ mud.
4. Spot 25 sacks cement at 4 1/2 stub at 1968' W.O.C. tag plug at 5' offill
5. Load hole w/ mud.
6. Spot 25 sacks cement at 1963'.
7. Spot 30 sacks cement at 1760' W.O.C. tag at 1652' 8 5/8 shoe
8. Spot 15 sacks cement at surface and set up P.A. marker.

Completed 5/7/92

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Peter W. Chester

TITLE Engineering Manager

DATE 6/19/92

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

Approved as to the safety of the well bore,
liability under bonding retained until
surface restoration is completed.

*See Instructions on Reverse Side

