

Form 9-331  
Dec. 1973

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Form Approved.  
Budget Bureau No. 42-R1424

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well ☐ gas well ☐ other
2. NAME OF OPERATOR  
El Ran, Inc.
3. ADDRESS OF OPERATOR  
P.O. Box 911, Lubbock, TX 79408
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: Unit Letter I, 1980' FSL & 1980' FEL  
AT TOP PROD. INTERVAL: same  
AT TOTAL DEPTH: 4360'
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:  
TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☒  
(other) ☐

SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

5. LEASE  
NM 13999A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Phillips Federal

9. WELL NO.  
#2

10. FIELD OR WILDCAT NAME  
Chaveroo Field JA

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Section 13, T8South, R32East

12. COUNTY OR PARISH  
Chaves

13. STATE  
N.M.

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
4433' G.L.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*
1. Set CIBP at 4213' and spot 35' cement plug on top.
  2. Run freepoint and cut casing off and pull 4 1/2 casing.
  3. Load hole with 9.5# mud and spot 100' cement plug across the 4 1/2 casing stub. Tag plug.
  4. Load hole with 9.5# mud and spot 100' cement plug from 1754' to 1654'.
  5. Load hole with 9.5# mud and spot a 50' cement plug at surface.
  6. Set marker and back rip location and road.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_

Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Robert R. Ramey TITLE Vice-President DATE 8/13/88

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY: \_\_\_\_\_

APPROVED  
PETER W. CHESTER

SEP 15 1988

BUREAU OF LAND MANAGEMENT

RECEIVED

SEP 22 1988

NOV 22 1988