	- .	N.M.O.C.D. COPI			
Form 9-331 May 1963: DEPARTMENT OF GEOLOGICA		NTERIOR (Other instructions on verse side)	5. LEASE DESIGNATION	au No. 42-R1424. AND SERIAL NO.	
	Y NOTICES AND REPORT OF PROPERTY OF THE PROPER	ORTS ON WELLS	6. IF INDIAN, ALLOTTE		
OIL WELL XOTWELL X			7. UNIT AGREEMENT N	7. UNIT AGREEMENT NAME	
2 NAME OF OPERATOR APR 2 5 1980			8. FARM OR LEASE NA	ME	
Anadarko Produci	ion Company	U.S. GEULUGICAL SURVEY	Frien	Friend Federal	
APTECIA NEW MEYICO			9. WELL NO.		
•	oco Hills, New Mexico			1	
4 TOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)			10. FIELD AND POOL, OR WILDCAT		
1980' FNL & 660' FWL Sec. 21, T13S, R31E Chaves County, New Mexico				Caprock Queen 11. sec., T., R., M., OR BLK. AND	
			SURVEY OR AREA		
			21 - 138	- 31E	
14 PERMIT NO.	15. ELEVATIONS (Show	whether DF, RT, GR, etc.)	12. COUNTY OR PARISI	H 13. STATE	
	4118.9	GL	Chaves	New Mexico	
6.			O.L. D.	· · · · · · · · · · · · · · · · · · ·	
		dicate Nature of Notice, Report,		•	
NOTI	CE OF INTENTION TO:	SU	ESEQUENT REPORT OF:		
TEST WATER SHUT-OFF	PULL OR ALTER CASING	WATER SHUT-OFF	REPAIRING	WELL	
FRACTURE TREAT	MULTIPLE COMPLETE	FRACTURE TREATMENT	ALTERING (
SHOOT OR ACIDIZE	ABANDON*	SHOOTING OR ACIDIZING	ABANDONME		
REPAIR WELL (Other)	CHANGE PLANS		(Other) Spud, set surf & Production csg K (Note: Report results of multiple completion on Well		
17 DESCRIBE PROPOSED OR COM	SPLETED OPERATIONS (Clearly state a	Il pertinent details and give pertinent d	completion Report and Log for	to of starting any	
proposed work. If welnent to this work.) *	l is directionally drilled, give subsu	urface locations and measured and true v	ertical depths for all market	rs and zones perti-	
1. Rigged up ro	tary tools.				
ran 8 joints @ 360' KB and w/2% CaCL.	8-5/8", 24#, K-55, 8 d baffle plate @ 318' PD @ 12:30 AM 4-18-80,	80; did not lose circula Rd, ST&C, Rge 3, Cond A KB. Halliburton cement, circulated 30 sx to pible Ram Hydraulic Blowou	casing; set casi ed with 225 sx Cl t. WOC - 6½ hour	ing shoe lass H	
3. WOC addition	al 5½ hours prior to	drilling casing shoe wit	h 7-7/8" bit.		
4. Drilled to 2	750°; did not run Dri	ll Stem Test.			
5. Ran Open Hol	e Logs.				
@ 2744' KB at		Rd, ST&C, Rge 3, Cond A ed with 350 sx Class C 5 . WOC			
Note: Will:	file appropriate form	s upon completion of wel	1.		

TITLE _

(This space for Federal or State office use)

APPROVED BY _______CONDITIONS OF APPROVAL, IF ANY:

Area Supervisor

April 23, 1980

DATE

APA . . 1906

RECEIVED

APR 28 1980

O. C. D.
ARTESIA, OFFICE

RECEIVED

APR 281980

OIL CONSERVATION DIV.