

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-85

SUNDRY NOTICES AND REPORTS ON WELLS <small>(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)</small>		5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Dry hole		5. State Oil & Gas Lease No.
Name of Operator NRM PETROLEUM CORPORATION		7. Unit Agreement Name
Address of Operator 900 Bldg. of the Southwest Midland, TX 79701		8. Farm or Lease Name Crosby
Location of Well UNIT LETTER D 660 FEET FROM THE west LINE AND 660 FEET FROM THE north LINE, SECTION 16 TOWNSHIP 7-S RANGE 31-E NMPM.		9. Well No. 1
15. Elevation (Show whether DF, RT, GR, etc.) 4329.3 GR		10. Field and Pool, or Wildcat Wildcat
		12. County Chaves

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> OTHER <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/> CHANGE PLANS <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/> COMMENCE DRILLING OPNS. <input type="checkbox"/> CASING TEST AND CEMENT JOBS <input type="checkbox"/> OTHER <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/> PLUG AND ABANDONMENT <input checked="" type="checkbox"/>

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

The Crosby #1 spudded 2-13-80 @ 4:30 a.m. Set 421' 8-5/8" surface csg. & cmt. w/250 sx Cl C w/2% CC. Drld. to 3867'. Cored 3867'-3994' (127') 3-2-80. Ran DST #1 3884-3994'. Rec. 61' drlg. mud. FSIP 980#. On 3-3-80 Welex ran open hole logs. On 3-5-80 set 30 sx Cl C plug @ 3994'-3884'; 30 sx plug @ 2997-2897'; 30 sx plug 1800-1700'; 30 sx plug 1500-1400'; 30 sx plug 475-375'; 10 sx plug @ surface. Released rig 2:00 a.m. 3-5-80. Well P & A.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

BY Cecil Tucker TITLE Operations Manager DATE 4-28-80
 BY A. H. Stettin TITLE OIL & GAS INSPECTOR DATE 5-1-80
 CONDITIONS OF APPROVAL, IF ANY: