

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPL
(Other instructions
verse side)E*
re-Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 0493690 3/263

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

RECEIVED

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Dalport Oil Corp.

3. ADDRESS OF OPERATOR

3471 First National Bank Bldg., Dallas, TX

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

660' FS & WL

APR 16 1980

O.C.D.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4034.7 gr

ARTESIA, OFFICE

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Holbrook Red-B Fed.

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Vest Ranch-On Assoc.

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

9-15S-30E

12. COUNTY OR PARISH

Chaves

13. STATE

N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐
☐

PULL OR ALTER CASING

☐
☐
☐
☐
☐

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐
☐
☐
☐
☐

REPAIRING WELL

☐
☐
☐
☐
☒

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other) Set produc. casing

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

4-5-80 Cored 2259-81 Rec. 21.3'
2295-61.3 Anhyd. & dolo.
-79 Red sand with oil show.
-81 Hard red sd & anhyd.

4-6-80 Dst. 2259-81 Open 1 hr.
Recov. 140' Sm & HGC oil, 15' SO & GCM.
FP 36-48, ISIP 109#/1', FSIP 109#/1'
HP 1207-1207.

4-6-80 TD 2348. Ran new 4½-9.5# J-55 casing to 2348. Float shoe on bottom of 20' joint, insert float at top of bottom joint. 3 scratchers and 3 centralizers/joint on 2nd, 3rd, 4th joints. Halliburton cemented with 125 sx lite, 150 sx 'C', 50% POZ, 2% gel, 8# salt/sack. Plug down 7:45 p.m.

18. I hereby certify that the foregoing is true and correct

SIGNED

George H. Stewart

TITLE Geologist

DATE 4-9-80

(This space for Federal or State office use)

100g. Bgd.) GEORGE H. STEWART

APPROVED BY

TITLE

DATE APR 14 1980

CONDITIONS OF APPROVAL, IF ANY: