

OIL CONSERVATION DIVISION

P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

3. Indicate Type of Lease  
State  For

5. State or Gas Lease No.  
L 4409

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG SALS TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT TO DRILL" (FORM C-101) FOR SUCH PROPOSALS.)

6. Indicate Well Type  
OIL WELL  GAS WELL  OTHER

1. Name of Operator  
Fred Pool Drilling Co. Inc.

2. Address of Operator  
Box 1399 Clovis Star Rt. Roswell, N.M. 88201

4. Location of Well  
UNIT LETTER P 660 FEET FROM THE S LINE AND 660 FEET FROM THE E LINE, SECTION 33 TOWNSHIP 8S RANGE 32 E N.M.P.M.

7. Unit Agreement Name

8. Form or Lease Name  
Opal

9. Well No.  
1

10. Field and Pool, or Wildcat  
Wildcat

12. County  
Chaves

15. Elevation (Show whether DF, RF, GR, etc.)  
4378 casing head

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPER. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
FULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Intend to shoot 4 1/2 casing off at top of cement and pull the casing.

Intend to place one 100 ft. cement plug across perforations from 4186 to 4232ft.

Also place one 100 ft. cement plug across the casing shoot off point.

Place one 100 ft. cement plug ( 35 sx) at the top of the San Andres, Queen, and Yates formations, at 3385 ft.; 2970 ft. and 2175 ft. respectively.

Also, one 100 ft. cement plug ( 35 sx) at the bottom of the 8 5/8 surface casing at 409 ft; fifty feet above and below the 8 5/8 casing shoe.

THE COMMISSION MUST BE NOTIFIED 24 HOURS PRIOR TO THE BEGINNING OF PLUGGING OPERATIONS FOR THE C-103 TO BE APPROVED.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Fred L. Pool III TITLE Petroleum Engineer DATE 6-3-81

APPROVED BY Jerry Sexton TITLE Dist L. Supv DATE JUN 8 1981

CONDITIONS OF APPROVAL, IF ANY: