N.M.O.C.D. COLY

	SUNDRY
	not use this f rvoir. Use For
1.	oit well
2.	NAME OF
	SUNDANCE
3.	ADDRESS
	<u>#510, 17</u>
4.	LOCATION
	below.)
	AT SURFAC
	AT TOP PF
	AT TOTAL
	(Do rese 1. 2. 3.

Form 9-331

Dec. 1973

UNITED STATES	Budget Bureau No. 42-R1424		
DEPARTMENT OF THE INTERIOR	5. LEASE		
	<u>NM-15678</u>		
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME '		
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepering the back to addite only reservoir. Use Form 9-331-C for such proposals.)	7. UNIT AGREEMENT NAME 8. FARM OR LEASE NAME		
1. oil well \square other AUG 2 7 1000	Ingram Federal 9. WELL NO.		
2. NAME OF OPERATOR SUNDANCE OIL COMPANY U.S. GLUDGURG SUNDANCE	13		
SUNDANCE OIL COMPANY ARTESIA, NEW MICHOO	10. FIELD OR WILDCAT NAME Tom-Tom, San Andres		
 #510, 1776 Lincoln St., Denver, CO 80203 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 1655' FNL, 2310' FEL, Unit G AT TOP PROD. INTERVAL: AT TOTAL DEPTH: Same 	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREASW NE Section 5, T.8S., R.31E.12. COUNTY OR PARISH Chaves13. STATE New Mexico14. API NO.		
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)		
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	4247' GL, 4259' KB		
TEST WATER SHUT-OFF	(NOTE: Report results of multiple completion or zone change on Form 9–330.)		
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state	all pertinent details, and give pertinent dates		

.

Form Approved.

******* •••

17. DESCRIBE —. including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* es,

-Herris

	an markers and zones pertinent to this	s wori	K.)*
Drilled to total depth of	3965' 8/18/80 Schlumbe	raar	r ran SNP and DLL-RXO logs.
Ran 127 its of 11" 10 5	$\# K_{-} \overline{55} C C C C C C C C C C C C C C C C C C $	a gei	Tan She and DEL-RAU TOgs.
Ran 127 jts. of $4\frac{1}{2}$, 10.5	π K-55 Casing. Set at 39	170 .	. Cemented with 300 sx
50/50 P02, 2% gel, 8# sal	t, I/4# cello flakes. Pl	ug c	lown at 5:15 p.m. 8/18/80.
Pressured up to 1000#, ok	ay. Released rig at 6:15	Ď.n	n. 8/18/80 Woru
		ρ	N. 07 107 00: NOCO: 2
			그 그 그 것 같아. 그는 것 같아. 한 생각이 있는 것 같아.
			· · · · · · · · · · · · · · · · · · ·
			제 그의 위에 비밀하지 않고 있었다.
			· · · · · · · · · · · · · · · · · · ·
Subsurface Safety Values Manus and T			지난민 나무는 수수는 붕 방법을
Subsurface Safety Valve: Manu. and Type			Set @ Ft.
18. I hereby certify that the foregoing is tru			김 비교 한 김 가 나 승규 했다.
- of the state of	e and correct		ျင့်ရှိဦးရ အဦး ဦးရွံကြားပြီး
SIGNED Manual Mult	TITLE V-P, Production		August 25 1000 2
		DATE	August 25, 1980
/	(This space for Federal or State office use)		ACCEPTED FOR RECORD
	,	1	
APPROVED BY	TITLE	DATE	관광되었는 회배는 동문주 이
CONDITIONS OF APPROVAL, IF ANY:			
			ALIG 2 9,1980
			A DOLLAR BUEV
			US GEOLOGICAL SURVEY
	*See Instructions on Reverse Side		ROSWELL, NEW MEXICO