Form 9–331 Dec. 1973	Form Approved.
UNITED STATES	Budget Bureau No. 42–R1424
DEPARTMENT OF THE INTERIOR	5. LEASE
GEOLOGICAL SURVEY	NM-15678
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SLINDRY NOTICES AND DEPORTS ON WELLS	7 11117 100
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	9 FARM OR LEADER WATER
1. oil NV gas	8. FARM OR LEASE NAME Ingram Federal
well XX well other	9. WELL NO.
2. NAME OF OPERATOR	113
SUNDANCE OIL COMPANY	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Tom-Tom, San Andres
#510, 1776 Lincoln St., Denver, CO 80203	11. SEC., T., R., M., OR BLK. AND SURVEY OF
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)	AREA
AT SURFACE: 1655' FNL, 2310' FEL, Unit G	SW NE Section 5, T.8S., R.31E.
AT TOP PROD. INTERVAL:	12. COUNTY OR PARISH 13. STATE
AT TOTAL DEPTH: Same	Chaves New Mexico
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	14. API NO.
REPORT, OR OTHER DATA	15
DECUECT FOR ADDRESS	15. ELEVATIONS (SHOW DF, KDB, AND WD) 4247' GL, 4259' KB
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	4247 JL, 4259 KB
TEST WATER SHUT-OFF FRACTURE TREAT	<b>n</b>
SHOOT OR ACIDIZE	
REPAIR WELL	2 g 7 g 3 g 3 g 3 g
PULL OR ALTER CASING   AUG 2 1980	(NOTE: Report results of multiple completion or zone change on Form 9-330.)
CHANGE ZONES   CHANGE	and the second of the second o
ABANDON*	
(other) SET SURFACE CASING ARTESIA, NEW MEXI	भूष्य । विश्व व
17 DESCRIPE PROPOSED OF COMPLETED	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is din measured and true vertical depths for all markers and zones pertinent	all pertinent details, and give pertinent dates,
measured and true vertical depths for all markers and zones pertinent	to this work,)*
Spudded 12 1/4" surface halo at 0 mm o (11/0)	
Spudded 12 1/4" surface hole at 8 p.m. 8/11/80.	Drilled to 1408'. Ran 38
jts. of 8 5/8", 24# surface casing. Set at 140 200 sx Class C cement w/2% CaCl. Plug down at up to 900#, okay Circulated 50 sw carrent w/2	18' W/200 sx 3% Lowdense &
up to 900#, okay. Circulated 50 sx cement. Wo for 30 minutes. okay	12:10 a.m. 8/13/80. Pressured
for 30 minutes, okay.	c. Pressured up on BOP to 1000#
•	
	그 그 그 그 이 살림을 하는 그는 사람들을 하는 것
	그는 그는 전통하는 그 등 지유교통
	그 그 그 그 이 생활하는 그 등 살 활활했다.
Subsurface Safety Valve: Manu. and Type	222345 TH 4533
18. I hereby certify that the foregoing is true and correct	Set @ Ft.
VISA ALAN / III T	
Richard O Damit V-P, Production	<u>n hate August 18, 1980</u>
(This space for Federal or State office	
APPROVED BY	ACCEPTED FOR RECORD
CONDITIONS OF APPROVAL, IF ANY:	PATE

**FIRST** 

\*See Instructions on Reverse Side