N.M.O.C.D. COY



United States Department of the Interior

GEOLOGICAL SURVEY

RECEIVED

P. O. Drawer U
Artesia, New Mexico 88210

JUL 9 1980

July 7, 1980 O. C. D.

ARTESIA, OFFICE

Exxon Corporation
Post Office Box 1600
Midland, Texas 79702

Gentlemen:

EXXON CORPORATION
Strange Federal No. 5
660 FSL 1980 FWL Sec. 25, T.7S, R.31E.
Chaves County Lease No. NM-15677-A

Above Data Required on Well Sign

Your APPLICATION FOR PERMIT TO DRILL the above-described well to a depth of 4,300 feet to test the San Andres formation is hereby approved subject to compliance with the OIL AND GAS OPERATING REGULATIONS (30 CFR 221) and the following conditions:

- Drilling operations authorized are subject to compliance with the GENERAL REQUIREMENTS FOR OIL AND GAS OPERATIONS ON FEDERAL LEASES, dated July 1, 1978.
- 2. Prior to commencing construction of road, pad, or other associated developments, operator will provide the dirt contractor with a copy of the SURFACE USE PLAN and this approval including the GENERAL REQUIREMENTS.
- 3. All access roads will be limited to a 12 foot wide driving surface, excluding turnarounds. Surface disturbance associated with road construction will be limited to 20 feet in width.
- 4. Submit a Daily Report of Operations from spud date until the Well Completion Report (form 9-330) is filed. The progress report should be not less than 8" x 5" in size and each page should identify the Well.
- 5. All permanent above-ground structures and equipment shall be painted in accordance with the attached Painting Requirements. The color used should simulate Sandstone Brown (Federal Standard No. 595A, color 20318 or 30318).
- 6. Notify the Survey by telephone 24 hours prior to spudding well.
- 7. Cement behind the 8-5/8" casing must be circulated.