

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 12-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☐ For ☒
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER	7. Unit Agreement Name
2. Name of Operator Coronado Exploration Corp.	8. Farm or Lease Name W. Cato
3. Address of Operator 1005 Marquette NW Albuquerque, New Mexico 87102	9. Well No. 1
4. Location of Well UNIT LETTER <u>H</u> <u>1980</u> FEET FROM THE <u>North</u> LINE AND <u>660</u> FEET FROM THE <u>East</u> LINE, SECTION <u>18</u> TOWNSHIP <u>8S</u> RANGE <u>30E</u> NMPM.	10. Field and Pool, or Wildcat Und. Cato SA
15. Elevation (Show whether DF, RT, GR, etc.) 4092.0 Gr.	12. County Chaves

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1408.

11-09-80 Set 4.5", 9.5# casing at 3360' with a regular pattern guide shoe, insert float, and 8 centralizers. Cemented with 125 sx Dowell Class "C" cement with 2% CaCl and 75 sx Dowell Self-Stress cement. Bumped plug and pressured casing to 300 psi, held pressure for 15 minutes noticing no drop in pressure. WOC. Estimated day to perforate - 11/24/80.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

CORONADO, EXPLORATION CORP.

SIGNED 107 tunnels TITLE Production Secretary DATE Nov. 19, 1980

APPROVED BY 107 tunnels TITLE Production Secretary DATE Nov. 19, 1980

RECEIVED
DEC 1 1986
OIL CONSERVATION DIV