

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N.M. Oil Cons. Division
1625 N. French Dr.
Hobbs, NM 88240

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Petroleum Development Corporation

3. Address and Telephone No.

4113 Eubank NE, Albuquerque, NM 87111 Suite 400 (505) 293-4044

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1/4 NESE S17 T8S R31E Unit I 1930' FSL 660' FEL

5. Lease Designation and Serial No.
NM067707

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

Unit I

8. Well Name and No.

Siete Federal #1

9. API Well No.

#1

10. Field and Pool, or Exploratory Area

San Andres

11. County or Parish, State

Chaves County, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

8/11/00

1. Loaded casing w/9# brine/mud
2. Set CIBP @ 3660' and dumped 5 sks. cement on top
3. Perforate @ 1830'
4. TIH w/packer--tag cement @ 3610'
5. Set packer @ 1757'-- pumped 30 sks. Class "C" cement w/2% caCl-displaced to 1777' w/9# brine/mud
6. T00H--perforate @ 1280'
7. TIH w/packer--set packer @ 1073'--pumped 55 sks. Class "C" cement w/2% CaCl--displace to 1093' w/9# brine/mud
8. TIH tag cement @ 1085'
9. Set 5 sk. surface plug
10. Install dry hole marker

14. I hereby certify that the foregoing is true and correct

Signed

Title Production Supervisor, NM

Date 8/22/2000

(This space for Federal or State office use)

Approved by

PETROLEUM ENGINEER

SEP 08 2000

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side

RECEIVED
AUG 2 2000
BLM
ROSWELL, NM

