

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

New Mexico 22635

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Apache Springs Unit

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat Miss.11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA**28-10-30**

12. COUNTY OR PARISH

Chaves

13. STATE

N.M.**SUNDRY NOTICES AND REPORTS ON WELLS**(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

DEPCO, Inc.

3. ADDRESS OF OPERATOR

800 Central, Odessa, Texas 797614. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface**K - 1780 FWL & 1980 FSL, Sec. 28, T10s, R30s**

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4057.8 GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

10-14-80 Spudded @ 11:00 AM. Drilled 17 1/2" hole to 346'. Ran 9 jts. 13 3/8" 54.50# csg. set @ 346'. Cemented w/375 sx. Class "C" w/2X Ca Cl. Plug down @ 9:15 PM. Circulated 25 sx. WOC.**10-15-80 Tested pipe and blowout preventers @ 1000# for 30 min. Tested OK.****10-18-80 Drilled 11" hole to 2865'. Ran 21 jts. 8 5/8" 32# 820.46', followed w/43 jts. 8 5/8" 24# 180.27', followed w/5 jts. 8 5/8" 32# 201.92' csg. Total 2810' set @ 2825'. Cmt. w/800 sx. pacesetter lite, 10# salt, 1/4# callo Flake. Followed w/200 sx. Class "C" neat. Plug down @ 4:30 PM. 10-19-80. Circ. 80 sx. WOC. Tested pipe and blowout preventers @ 1000# for 30 min. Tested OK.**

RECEIVED

OCT 27 1980

U.S. GEOLOGICAL SURVEY
ALBUQUERQUE, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED R. L. Denny **R. L. DENNEY**TITLE **Chief Clerk**DATE **10-24-80**

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, **OCT 30 1980**

TITLE

DATE

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

GPO 680-160

RECEIVED

NOV 5 1980

OIL CONSERVATION DIV.