

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐
2. NAME OF OPERATOR
SUNDANCE OIL COMPANY
3. ADDRESS OF OPERATOR
#910, 1776 Lincoln St., Denver, CO 80203
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 660' FSL, 1980' FWL, Unit N
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	<input type="checkbox"/>		<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>		<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>		<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>		<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>		<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>		<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>		<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>		<input type="checkbox"/>
(other) SET SURFACE CASING	<input type="checkbox"/>		<input type="checkbox"/>

5. LEASE
NM-15678
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Ingram Federal
9. WELL NO.
16
10. FIELD OR WILDCAT NAME
Tom-Tom, San Andres
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
SE SW Section 5, T.8S., R.31E.
12. COUNTY OR PARISH
Chaves
13. STATE
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
4226' GL, 4238' KB

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 12-1/4" surface hole at 12:30 p.m. on 5/9/81. Drilled to 1350'. Ran 33 jts. of 8 5/8", 24#, K-55 surface casing. Set at 1350' KB. Cemented w/300 sx 3% Econolite and 200 sx Class C, 2% CaCl₂. Circulated 97 sx. PD at 2:30 p.m. on 5/11/81. Pressured up to 700#, okay. WOC.

RECEIVED
MAY 26 1981
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

Subsurface Safety Valve: Manu. and Type _____

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Burt Aycock TITLE Executive V-P DATE May 20, 1981

APPROVED BY
CONDITIONS OF

ACCEPTED FOR RECORD
ROGER A. CHAPMAN
(This space for Federal or State office use)

APPROVAL, IF ANY:

MAY 26 1981

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side