Form 9-331 Dec. 1973 UNITED STATES NEW MEXICO 832	
DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY	NM-15678 6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different	7. UNIT AGREEMENT NAME
reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME Ingram Federal
well well other DRY	9. WELL NO. 18
2. NAME OF OPERATOR SUNDANCE OIL COMPANY	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR #910, 1776 Lincoln St., Denver, CO 80203	Tom-Tom, San Andres 11. SEC., T., R., M., OR BLK. AND SURVEY OR
 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 660' FNL, 1980' FEL, Unit B AT TOP PROD. INTERVAL: AT TOTAL DEPTH: Same 	AREA <u>NW NE Section 8, T.8S., R.31E.</u> 12. COUNTY OR PARISH 13. STATE <u>Chaves</u> 14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	15. ELEVATIONS (SHOW DF, KDB, AND WD) 4230' GL, 4242' KB
TEST WATER SHUT-OFF	(NOTE: Report readies a maripra competion prison change the form 9-330.) UUN 2 1931 OIL & GAS U.S. GEOLOGICAL SURVEY ROSWELL NEW MEXICO
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*	
Received verbal approval to plug from Jim Gillham on 6/15/81. Halliburton set cement plugs as follows (Class H cement):	
45 sx from 3753-3653' 45 sx from 3040-2940' 45 sx from 1395-1295' 10 sx from 0-20'	
Rig released at 5 a.m. on 6/16/81. Preparing to set dry hole marker, the backfill pits & level location.	
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I hereby certify that the foregoing is true and correct SIGNED	ary6/18/81
APPROVED BY CONDITIONS OF SAPERBEALE DE WAY CHESTER	fice use)
APPROVED. BY	UAIL
.1985	
*See Instructions on Reverse	Side

.

