

N. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
SEE APPLICATION FOR PERMIT - (FORM C-101) FOR SUCH PROPOSALS.

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator Adams Exploration Company
3. Address of Operator P. O. Box 10585, Midland, Texas 79702
4. Location of Well UNIT LETTER <u>F</u> <u>2030'</u> FEET FROM THE <u>North</u> LINE AND <u>1980</u> FEET FROM THE <u>West</u> LINE, SECTION <u>10</u> TOWNSHIP <u>8-S</u> RANGE <u>32-E</u> NMPM

7. Unit Agreement Name
8. Farm or Lease Name Griffin
9. Well No. 2
10. Field and Pool, or Wildcat Undesignated Chaveroo/San Andres
12. County Chaves

15. Elevation (Show whether DF, RT, GR, etc.)

4469.3 GR

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spud 12 1/4" surface hole 4-28-81. Drld to TD 1850' 5-1-81. Ran 8 5/8" csg to 1850'. Cmt'd w/600 sx Pacesetter Lt Wt w/10# salt/sk plus 1/4# celosele, followed by 200 sx Class-C w/2% CaCl. Circ'd .258 sx to pit. PD 5-1-81. Drld 7 7/8" hole to TD 4285' as of 5-9-81. Ran 107 jts 4 1/2", 10.5#, ST&C csg to TD 4284', cmt'd w/ 400 sx Class-C, 50:50 Poz w/8# salt/sk, 2% gel & 4/10% Westerns 7F-4 & 2/10% Western AF-11, slurry 14.8#. PD w/1000 psi 5-5-81. Set slips, cut off 4 1/2" csg. Released rig 5-9-81.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Dr. Helm TITLE Operations Manager DATE 6-22-81

Orig. Signed by

Larry Sexton

DATE 6-22-81

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: