

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

N.M.O.C.D. COPY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

USA NM 16637

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

RECEIVED

1. OIL ☒ GAS ☐
WELL WELL OTHER

2. NAME OF OPERATOR

Flag-Redfern Oil Company

3. ADDRESS OF OPERATOR

P. O. Box 2280, Midland, Texas 79702

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface 660' FSL & 330' FEL

SEP 4 1981

O. C. D.

ARTESIA, OFFICE

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Hahn ~~Federal~~ "A" Fed,

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

Tom-Tom (San Andres)

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 28, T-7-S, R-31-E

12. COUNTY OR PARISH 13. STATE

Chaves

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

Running Casing

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

7/6/81 Ran 35 jts 8 5/8" 24 lb K-55 ST&C casing. Set at 1442'. Cemented with 600 sx Hal Light with 1/4 lb flocele, 8 lb salt and 200 sx Class "C" 2/ 2% CaCl. Plug down 10:30 PM 7/5/81. WOC 16 hours. Test casing to 1000 psi for 30 minutes. **CIRC.**

7/13/81 Ran 106 jts 4 1/2" 9.50 K-55 casing. Set at 4120'. Float collar 4081. Cemented with 250 sx 50-50 Class "H" Poz with 2% gel, 8 lb salt, 0.75% CFR-Z. Plug down at 2:00 PM Released Rig at 4:00 PM 7/12/81.

SEP 4 1981

U.S. GEOLOGICAL SURVEY
MIDLAND, TEXAS

18. I hereby certify that the foregoing is true and correct

SIGNED

ROGER A. CHAPMAN

TITLE Engineer

DATE 9/1/81

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

U.S. GEOLOGICAL SURVEY

ROSWELL, NEW MEXICO

*See Instructions on Reverse Side

RECEIVED

SEP 8 1981

OIL CONSERVATION DIV