

REPORT OF
SUB-SURFACE
DIRECTIONAL
SURVEY

API #

PETROLEUM DEVELOPMENT CORPORATION

WATTAM FEDERAL NO. 1

CHAVES COUNTY, NEW MEXICO

B-5-2-71

JOB NUMBER

430-1662

430-1662

TYPE OF SURVEY

GYROSCOPIC

STEERING TOOL

DATE

DECEMBER 10, 1993

DECEMBER 14, 1993

SURVEY BY TIM STEPHENS/RON COLLINS

OFFICE: MIDLAND, TX

PETROLEUM DEVELOPEMENT CORPORATION

Structure : WATTAM FEDERAL #1





Field : TOM TOM

Location : CHAVES COUNTY, NEW MEXICO

Point	MD	Inc	Dir	TVD	North	East
Flow on	0	0.00	45.00	0	0	0
KOP	3630	0.00	45.00	3630	0	0
End of Build	3756	90.00	45.00	3710	56	56
Target	4466	90.00	45.00	3710	560	380

Scale 1 : 50.00

East -->



PETROLEUM DEVELOPEMENT CORPORATION
WATTAM FEDERAL #1

slot #1
TOM TOM
CHAVES COUNTY, NEW MEXICO

SURVEY LISTING

by
Baker Hughes INTEQ

Your ref :
Our ref : svy242
License :

Date printed : 28-Dec-93
Date created : 3-Dec-93
Last revised : 28-Dec-93

Field is centred on 0.000,0.000,0.00000,+
Structure is centred on 0.000,0.000,0.00000,N

Slot location is n0 0 0.000,w4 29 18.843
Slot Grid coordinates are N 0.000, E 0.000
Slot local coordinates are 0.00 N 0.00 E
Reference North is Grid North

PETROLEUM DEVELOPEMENT CORPORATION
WATTAM FEDERAL #1,slot #1
TOM TOM,CHAVES COUNTY, NEW MEXICO

SURVEY LISTING Page 1
Your ref :
Last revised : 28-Dec-93

Measured Depth	Inclin. Degrees	Azimuth Degrees	True Vert. Depth	R E C T A N G U L A R C O O R D I N A T E S	Dogleg Deg/100Ft	Vert Sect
0.00	0.00	0.00	0.00	0.00 N	0.00 E	0.00
100.00	0.47	154.65	100.00	0.37 S	0.18 E	-0.14
200.00	0.31	168.19	200.00	1.01 S	0.41 E	-0.42
300.00	0.15	177.27	300.00	1.40 S	0.47 E	-0.66
400.00	0.17	298.88	400.00	1.46 S	0.34 E	-0.79
500.00	0.50	312.39	499.99	1.09 S	0.11 W	-0.85
600.00	0.44	309.60	599.99	0.56 S	0.72 W	-0.91
700.00	0.54	327.08	699.99	0.08 N	1.28 W	-0.84
800.00	0.56	312.71	799.98	0.81 N	1.89 W	-0.76
900.00	0.38	308.91	899.98	1.35 N	2.51 W	-0.82
1000.00	0.42	324.24	999.98	1.86 N	2.98 W	-0.80
1100.00	0.44	329.21	1099.97	2.48 N	3.39 W	-0.64
1200.00	0.28	338.03	1199.97	3.04 N	3.68 W	-0.45
1300.00	0.42	318.29	1299.97	3.54 N	4.02 W	-0.34
1400.00	0.39	312.52	1399.97	4.04 N	4.51 W	-0.33
1500.00	0.43	298.72	1499.96	4.45 N	5.09 W	-0.45
1600.00	0.41	316.55	1599.96	4.89 N	5.67 W	-0.54
1700.00	0.55	306.34	1699.96	5.44 N	6.30 W	-0.61
1800.00	0.54	306.10	1799.95	6.00 N	7.07 W	-0.75
1900.00	0.56	304.73	1899.95	6.56 N	7.85 W	-0.91
2000.00	0.82	349.32	1999.94	7.54 N	8.38 W	-0.60
2100.00	0.95	4.09	2099.93	9.07 N	8.46 W	0.43
2200.00	1.11	11.76	2199.91	10.84 N	8.20 W	1.87
2300.00	1.14	7.28	2299.90	12.78 N	7.88 W	3.47
2400.00	1.06	12.20	2399.88	14.67 N	7.55 W	5.03
2500.00	1.03	5.84	2499.86	16.47 N	7.27 W	6.50
2600.00	0.93	10.42	2599.84	18.16 N	7.03 W	7.87
2700.00	1.10	6.11	2699.83	19.91 N	6.78 W	9.28
2800.00	0.93	0.38	2799.81	21.68 N	6.67 W	10.61
2900.00	1.07	355.40	2899.80	23.42 N	6.74 W	11.79
3000.00	0.82	343.23	2999.78	25.04 N	7.02 W	12.74
3100.00	0.71	354.05	3099.78	26.34 N	7.29 W	13.46
3200.00	0.65	349.18	3199.77	27.51 N	7.46 W	14.17
3300.00	0.60	357.31	3299.76	28.59 N	7.60 W	14.84
3400.00	0.53	347.37	3399.76	29.56 N	7.72 W	15.45
3500.00	0.38	311.02	3499.76	30.23 N	8.07 W	15.67
3600.00	0.52	313.76	3599.75	30.77 N	8.65 W	15.64
3630.00	3.55	10.68	3629.73	31.77 N	8.58 W	16.40
3635.00	4.10	11.70	3634.72	32.10 N	8.51 W	16.68
3645.00	7.70	13.50	3644.66	33.10 N	8.28 W	17.55
3650.00	10.70	181.80	3649.64	32.96 N	8.22 W	17.50
3655.00	14.30	6.90	3654.60	33.12 N	8.16 W	17.65
3660.00	16.10	359.40	3659.42	34.42 N	8.09 W	18.62
3665.00	18.20	353.00	3664.20	35.89 N	8.19 W	19.58
3670.00	20.90	349.70	3668.91	37.54 N	8.45 W	20.57
3675.00	24.10	344.60	3673.53	39.41 N	8.88 W	21.58
3680.00	27.70	340.30	3678.03	41.48 N	9.54 W	22.59
3685.00	30.70	339.70	3682.40	43.78 N	10.38 W	23.62
3690.00	34.20	341.40	3686.61	46.31 N	11.27 W	24.78
3695.00	38.10	342.10	3690.65	49.11 N	12.19 W	26.10

All data is in feet unless otherwise stated
Coordinates from structure and TVD from wellhead.
Vertical section is from N 0.00 E 0.00 on azimuth 45.00 degrees.
Declination is 0.00 degrees, Convergence is 0.00 degrees.
Calculation uses the minimum curvature method.
Presented by Baker Hughes INTEQ

PETROLEUM DEVELOPEMENT CORPORATION
WATTAM FEDERAL #1, slot #1
TOM TOM, CHAVES COUNTY, NEW MEXICO

SURVEY LISTING Page 2
Your ref :
Last revised : 28-Dec-93

Measured Depth	Inclin. Degrees	Azimuth Degrees	True Vert. Depth	R E C T A N G U L A R C O O R D I N A T E S		Dogleg Deg/100Ft	Vert Sect
3700.00	43.40	342.50	3694.44	52.22 N	13.18 W	106.13	27.60
3705.00	47.00	341.80	3697.96	55.59 N	14.27 W	72.68	29.22
3710.00	50.90	340.80	3701.24	59.16 N	15.48 W	79.44	30.89
3715.00	54.60	338.60	3704.27	62.89 N	16.86 W	81.86	32.55
3720.00	58.80	336.60	3707.01	66.76 N	18.46 W	90.40	34.15
3725.00	63.70	335.10	3709.42	70.75 N	20.25 W	101.46	35.71
3730.00	68.10	334.40	3711.46	74.88 N	22.20 W	88.92	37.25
3735.00	72.40	333.80	3713.15	79.11 N	24.25 W	86.74	38.79
3740.00	76.20	333.20	3714.50	83.42 N	26.40 W	76.87	40.32
3745.00	80.90	331.90	3715.49	87.77 N	28.66 W	97.39	41.80
3750.00	85.40	331.50	3716.09	92.14 N	31.01 W	90.35	43.22
3755.00	90.40	331.90	3716.27	96.53 N	33.38 W	100.32	44.66
3756.00	90.50	331.91	3716.26	97.42 N	33.85 W	10.05	44.95
3765.00	91.40	332.00	3716.12	105.36 N	38.08 W	10.05	47.57
3775.00	91.60	332.60	3715.85	114.21 N	42.73 W	6.32	50.54
3785.00	91.30	333.10	3715.60	123.10 N	47.29 W	5.83	53.61
3795.00	91.70	333.70	3715.34	132.04 N	51.76 W	7.21	56.76
3805.00	91.30	333.90	3715.08	141.01 N	56.18 W	4.47	59.99
3815.00	91.10	334.80	3714.87	150.02 N	60.51 W	9.22	63.30
3825.00	89.80	334.80	3714.79	159.07 N	64.76 W	13.00	66.68
3835.00	88.70	334.40	3714.92	168.10 N	69.05 W	11.70	70.04
3845.00	89.10	335.80	3715.11	177.17 N	73.26 W	14.56	73.48
3855.00	91.40	337.70	3715.07	186.36 N	77.21 W	29.83	77.18
3865.00	92.20	340.20	3714.75	195.69 N	80.80 W	26.24	81.24
3875.00	91.70	341.30	3714.41	205.12 N	84.09 W	12.08	85.58
3885.00	92.30	342.70	3714.06	214.63 N	87.18 W	15.22	90.12
3895.00	94.40	343.00	3713.48	224.17 N	90.13 W	21.21	94.78
3905.00	94.50	344.20	3712.70	233.73 N	92.94 W	12.00	99.55
3915.00	94.60	345.00	3711.91	243.34 N	95.59 W	8.04	104.48
3925.00	94.80	344.50	3711.09	252.96 N	98.21 W	5.37	109.42
3935.00	94.60	346.80	3710.27	262.61 N	100.68 W	23.01	114.50
3945.00	95.50	348.10	3709.39	272.33 N	102.84 W	15.77	119.85
3955.00	97.30	348.40	3708.28	282.06 N	104.87 W	18.24	125.30
3965.00	98.50	348.90	3706.90	291.77 N	106.82 W	12.98	130.78
3975.00	97.60	348.90	3705.50	301.49 N	108.72 W	9.00	136.31
3985.00	97.40	349.20	3704.20	311.22 N	110.61 W	3.58	141.86
3995.00	97.20	350.50	3702.93	320.99 N	112.35 W	13.05	147.52
4005.00	96.00	351.80	3701.78	330.80 N	113.88 W	17.63	153.38
4015.00	95.10	352.00	3700.81	340.66 N	115.28 W	9.22	159.36
4025.00	92.80	350.80	3700.12	350.52 N	116.78 W	25.93	165.28
4035.00	89.20	349.60	3699.95	360.37 N	118.48 W	37.95	171.04
4045.00	88.50	348.80	3700.15	370.19 N	120.35 W	10.63	176.66
4055.00	87.70	349.00	3700.48	380.00 N	122.28 W	8.24	182.24
4065.00	87.00	349.50	3700.94	389.81 N	124.14 W	8.60	187.86
4075.00	89.40	350.30	3701.26	399.65 N	125.89 W	25.30	193.58
4085.00	93.10	353.20	3701.04	409.54 N	127.33 W	47.00	199.56
4095.00	94.60	354.90	3700.37	419.46 N	128.36 W	22.64	205.84
4105.00	94.50	355.90	3699.57	429.40 N	129.16 W	10.02	212.30
4115.00	93.10	356.60	3698.91	439.36 N	129.81 W	15.64	218.88
4125.00	93.10	355.50	3698.37	449.32 N	130.50 W	10.98	225.44

All data is in feet unless otherwise stated
Coordinates from structure and TVD from wellhead.
Vertical section is from N 0.00 E 0.00 on azimuth 45.00 degrees.
Declination is 0.00 degrees, Convergence is 0.00 degrees.
Calculation uses the minimum curvature method.
Presented by Baker Hughes INTEQ

PETROLEUM DEVELOPEMENT CORPORATION
WATTAM FEDERAL #1,slot #1
TOM TOM,CHAVES COUNTY, NEW MEXICO

SURVEY LISTING Page 3
Your ref :
Last revised : 28-Dec-93

Measured Depth	Inclin. Degrees	Azimuth Degrees	True Vert. Depth	R E C T A N G U L A R C O O R D I N A T E S		Dogleg Deg/100Ft	Vert Sect
4135.00	90.50	356.80	3698.06	459.29 N	131.17 W	29.06	232.02
4145.00	88.40	356.40	3698.15	469.27 N	131.76 W	21.38	238.65
4155.00	86.40	358.70	3698.60	479.25 N	132.19 W	30.46	245.41
4165.00	85.70	359.00	3699.29	489.23 N	132.39 W	7.61	252.32
4175.00	85.70	359.00	3700.04	499.20 N	132.57 W	0.00	259.25
4185.00	84.60	359.60	3700.89	509.16 N	132.69 W	12.52	266.21
4195.00	83.00	1.10	3701.97	519.10 N	132.63 W	21.87	273.28
4205.00	81.00	1.90	3703.36	529.00 N	132.37 W	21.51	280.46
4231.00	75.80	3.96	3708.59	554.42 N	131.07 W	21.45	299.36 TD. PROJECTED F/ PREVIOUS SURVEY

All data is in feet unless otherwise stated
Coordinates from structure and TVD from wellhead.
Vertical section is from N 0.00 E 0.00 on azimuth 45.00 degrees.
Declination is 0.00 degrees, Convergence is 0.00 degrees.
Calculation uses the minimum curvature method.
Presented by Baker Hughes INTEQ

PETROLEUM DEVELOPEMENT CORPORATION
WATTAM FEDERAL #1,slot #1
TOM TOM,CHAVES COUNTY, NEW MEXICO

SURVEY LISTING Page 4
Your ref :
Last revised : 28-Dec-93

				Comments in wellpath
				=====
MD	TVD	Rectangular Coords.		Comment

3600.00	3599.75	30.77 N	8.65 W	GYRO F/ SURFACE
3630.00	3629.73	31.77 N	8.58 W	SHORT RADIUS KOP
3756.00	3716.26	97.42 N	33.85 W	GIH W/ ANGLE HOLD MOTOR
4231.00	3708.59	554.42 N	131.07 W	TD. PROJECTED F/ PREVIOUS SURVEY

All data is in feet unless otherwise stated
Coordinates from structure and TVD from wellhead.
Bottom hole distance is 569.71 on azimuth 346.70 degrees from wellhead.
Vertical section is from N 0.00 E 0.00 on azimuth 45.00 degrees.
Declination is 0.00 degrees, Convergence is 0.00 degrees.
Calculation uses the minimum curvature method.
Presented by Baker Hughes INTEQ



2105 Market Street Midland, Texas 79703
915-694-9517 Fax 915-694-5648

SURVEY CERTIFICATION SHEET

STATE OF TEXAS
COUNTY OF MIDLAND

I, Tim Stephens, in the employ of Baker Hughes INTEQ did on the days of December 10, 1993 thru December 10, 1993 conduct or supervise the taking of a Gyroscopic survey by the method of magnetic orientation from a depth of 0 feet to 3600 feet, with recordings of inclination and direction being obtained at approximate intervals of 100 feet.

This survey was conducted at the request of Petroleum Development Corporation for their Wattam Federal No. 1, Chaves County, State of New Mexico.

The data for this survey and the calculation were obtained and performed by me according to standards and procedures as set forth by Baker Hughes INTEQ and is true and correct to the best of my knowledge.

Tim Stephens
Directional Supervisor/Surveyor



2105 Market Street Midland, Texas 79703
915-694-9517 Fax 915-694-5648


SURVEY CERTIFICATION SHEET

STATE OF TEXAS
COUNTY OF MIDLAND

I, Ron Collins, in the employ of Baker Hughes INTEQ did on the days of December 10, 1993 thru December 14, 1993 conduct or supervise the taking of a Steering Tool survey by the method of magnetic orientation from a depth of 3635 feet to 4055 feet, with recordings of inclination and direction being obtained at approximate intervals of 5 feet.

This survey was conducted at the request of Petroleum Development Corporation for their Wattam Federal No. 1, Chaves County, State of New Mexico.

The data for this survey and the calculation were obtained and performed by me according to standards and procedures as set forth by Baker Hughes INTEQ and is true and correct to the best of my knowledge.



Directional Supervisor/Surveyor

